

SK-300 & SK-500 Series



8 & 16 Port USB KVM Switch

FEATURES:

- 8 or 16 Ports (DB-15 or Cat6 connectors)
- Control multiple systems from one point
- Hot Pluggable, no need to power down
- Support resolutions up to 1920 x 1200
- Slim 1U size, 1.75" high
- OS Support: Windows / Linux / Unix / Mac
- Optional 12/24/48/125/250V DC power
- Optional Remote IP

SPECIFICATIONS:

Construction & Design 1U , 1.75" or 44.5mm high

KVM Specification: 8 or 16 Ports
Connector: DB-15 or Cat6
Connectivity: Combo 2-in-1
VGA + USB KVM cable, 6 feet
USB Hub: 2 x USB type A for sharing other peripheral devices among the computers

Power: Operating Temperature: 0~55C (32~131F)
Operating Relative Humidity (non condensing) 20-90%
Storage Relative Humidity (non condensing) 5-90%
Operating Temperature: 0~50C (32~122F)
Storage Temperature: -20~60C (-4~140F)
Shock: 10G acceleration (11ms duration)
Vibration: 5~500Hz 1G RMS random vibration

Native Resolution: 16:10 Aspect Ratio (Max. 1920 x 1200)
4:3 Aspect Ratio (Max. 1600 x 1200)

Controls On-Screen: Language, Hotkey, Security

Input: Power Consumption: Max. 10W

Unit Weight: 6.5 lbs / 3 kg

Additional Options: DC Power Input – 12V (9-18), 24V (18-36), 48V (36-75), 125V (66-160), 250V (180-425)
Remote IP connectivity

Warranty: 2 Year limited Warranty Standard

WWW.SPARTONRE.COM | SALES@SPARTONRE.COM

Please contact your sales representative for more information.
Consult Factory on pricing and lead time.