

LPC-480PCIEG4 - POWERFUL MINI PC WITH PCIE X4 SLOT EXPANSION (DISCONTINUED)



A Small PC with open PCIe x4 expansion slot

- Powerful Intel Core i7 Mobile Processor
- PCIe Slot Support one PCIe x4 card
 - Small Size for Easy Deployment
- 10-26 VDC Operation, ideal for mobile/field
- Built-in 4 Gigabit LAN, 4 USB 3.0, Audio, Serial, Video
 - Low Profile Rugged Aluminium Chassis
 - Slim Slot Loading Optical Drives
 - Solid State Hard Drives (SSD) optional
- Windows 10, 8.1 & 7 Compatible, *other O/S Options Available
 - PCIe x4 Slot version also available

The LPC-480PCleG4 is now end of life with limited stock remaining. The new functional equivalent model the LPC-490E can be found here.





GALLERY IMAGES







PRODUCT DESCRIPTION

Add your PCIe x4 card slot in a powerful small form computer

Stealth's Little PC serves up Power, Performance and the ability to install your own PCIe x4 expansion card right into the machine without compromising space. The LPC-480PCIeG4 delivers the ultimate in performance utilizing an impressive Intel 3rd Generation Core i7 Processor. The LPC-480PCIeG4 small pc also features unprecedented network connectivity with 3-Front & 1-Rear Gigabit LAN Network Ports. Ideal for numerous applications such as data acquisition, control, specialized graphics cards and expanded I/O cards.

The Stealth LPC-480 series Little PC is packed with features including a front slot loading optical drive, 4 USB 3.0, 2 RS232/Serial, Gigabit LAN ports, 2.5" mobile hard drive with up to 1TB of capacity or SSD options, up to 16GB of memory, Intel HD graphics, audio in/out and much more.



ADDITIONAL INFORMATION

Processor

Supporting Intel® 3rd Generation Core™ i7 Processor 3610QE or

Intel® Celeron Dual-Core 1020E (standard)

Chipset Intel HM76 (Panther Point)

BIOS Insyde UEFI BIOS

Memory 4GB DDR3 (standard), options of 8 and 16GB available

SATA III (6Gb/s and 3Gb/s) support

Internal Storage

Offered with 500GB Serial ATA (SATA) with options of up to 1TB

capacity

Optional Solid State Disk Drive (SSD)

Expansion Slot(s)1 x PCle x4 Version 2.0 Compliant card up to 8.5"

Supports both x4 and x1 PCle cards

Optical Drives

Optional Slim DVD-RW / CD-RW (SATA)

Optional DVD-RW / Blu-Ray Burner Serial ATA (SATA)

Dual Display support (clone or extended desktop)

Video Integrated Intel HD graphics i7-3610QE CPU: Intel HD4000 B840

CPU: Intel HD3000

Includes VGA / HD-15 port and DVI-D (digital Only)

Networking

Integrated 10/100/1000 Base-T Intel Pro 1000 PL (82574L)

Gigabit Ethernet controller, RJ45 connection (PXE support)

Audio Integrated Realtek High Definition Audio CODEC ALC892

Windows 10 (64-bit)

Windows 7 (32 and 64-bit) Windows 8.1 (32 and 64-Bit) Windows 8 (32 and 64-Bit)

Operating Systems Windows Server 2008

Windows Server 2012 R2

Ubuntu Linux

Optional: QNX & embedded

Please contact us directly for any special requirements

Chassis Description Rugged Aluminum Chassis



Power Input

Rear 12VDC power Jack ideal for mobile applications

Includes External AC Adapter, Input 100~240V AC @ 1.5A

50-60Hz

Input is 10-26VDC +/-5% @ 7A (84W)

ACPI 4.0a compliant and Operating System direct power

management

Power Management

Wake-on event (Real Time Clock / RTC, USB Keyboard, LAN /

Network, Keyboard, Mouse)

Processor temperature

Hardware Monitor Cooling fan speed

Voltage

100-240V AC Adapter

North American Power Cord

Included with System

4 Rubber Feet

DVD Playback Software CD Burning Software

* NOTE: Subject to change without notice

Remote power option Ideal for OEM or Cabinet manufacturers

Options Solid State Drives (SSD) SATA

Wall Mount Bracket

2 PS/2 ports for Keyboard & Mouse

2x RS232 COM port

1x Gigabit RJ45 Network connection

Audio Line-Out Jack

Rear Panel 2 x USB 2.0 Ports

1x Analog VGA / HD-15 1x DVI-D video connector

DC Power Input Jack

PCle x1 1.1 Compliant expansion Slot

4 x USB 3.0 Ports *

3 x 10/100/1000 RJ45 Network connections

Microphone Input Jack

Power and Hard Drive notification LED

Front Panel Power-on button

Reset button

* Note: The Intel® USB 3.0 eXtensible Host Controller Driver is not supported on Windows XP and Windows Vista, USB 2.0

speeds will be used

Dimensions 5.8" (W) x 10.0" (D) x 2.8" (H) (147 x 250 x 71 mm)



Operating Temperature: -10 to 45C **Environmental**

Storage Temperature: -20 to 60C

Relative Humidity: 20% ~ 90% (Operating & Non-Operating)

RoHS

CE **Approvals**

FCC

Shipping Weight: 6.5 Lbs / 2.9 KG (Depending on configuration) Weight

Unit Weight: 3.45 lbs / 1.56 KG (Depending on configuration)

Power supply Weight: 1.35 lbs / 0.62 KG

1 Year limited Warranty Standard Warranty

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer Note: Specifications are subject to change without notice.

> Page: 5 May 14, 2024