

## LPC-140G4 - ULTRA SMALL MINI PC WITH 4 GIGABIT LAN PORTS



**\$1,045.00 USD**

### ***4-Gigabit Ethernet Ports in the palm of your hand!***

- 4 Gigabit Ethernet LAN/WAN ports
- Ultra Small, Only 4.0" x 6.1" x 1.5" in size
  - Powerful Intel Mobile Processors
- 10-26 VDC Operation, Ideal for Mobile/Field
  - Up to 2TB Internal Storage
  - SSD (Solid State Drive) Optional
- Built-in GB LAN, USB 3.0/2.0, Audio, Serial, Video
  - Low Profile Rugged Aluminium Chassis
  - Panel/Wall Mount Brackets Included
- Windows 7, 10 Compatible, \*other O/S Options Available

**The LPC-140G4 model is now end of life with limited stock remaining. Please contact us for availability or replacement options.**





## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth LPC-140G4 Multi-LAN Ultra Small Mini PC features a total of 4 GB Ethernet ports all in one tiny machine measuring (4.0" x 6.1" x 1.45") or just a little larger than a deck of playing cards.

The LPC-140G4 is a powerful, feature rich small-form PC that harnesses the power Intel's 4th generation i3 and Celeron mobile processors. Ideal applications include; security, VPN, network appliance, bandwidth controller, network diagnostics, IoT (Internet of Things), mini servers and more.

The LPC-140G4 operates from an external AC power adapter (included) or can be connected to an external 10-26 VDC source making it ideal for mobile and remote applications.

Stealth's LittlePCs are small form factor mini PCs designed to fit in space-confined areas and are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Transportation, mining and Telecommunications markets.

## ADDITIONAL INFORMATION

<b>Processor</b>	Supporting Intel® 4th Generation Core™ i3 Processor 4010U or Intel® Celeron Dual-Core 2980U (standard)
<b>Chipset</b>	8-series chipset integrated in CPU
<b>BIOS</b>	Insyde UEFI BIOS
<b>Memory</b>	Offers 2 x DDR3 SO-Dimm memory slots providing options up to 16GB of RAM
<b>Internal Storage</b>	Offered with 500GB Serial ATA (SATA) with options of up to 2TB capacity Optional Solid State Disk Drive (SSD) mSATA drive support via 1 Internal Mini-PCle
<b>Internal Expansion Option</b>	1 Internal Mini-PCle expansion option PCle and USB devices supported
<b>Video</b>	Onboard/Integrated Intel HD Graphics (built into the CPU) Dual Display support (clone or extended desktop) 3x Integrated 10/100/1000 Base-T Intel (i210-AT) Gigabit Ethernet controller, RJ45 connection (PXE support) 1x Integrated 10/100/1000 Base-T Intel (i218LM) Gigabit Ethernet controller, RJ45 connection (PXE support)
<b>Networking</b>	Optional Built in 802.11 ac/a/b/g/n Wireless Networking Card, Dual Band Support, 2.4Ghz / 5Ghz + Bluetooth via Mini-PCle, Intel AC 7260
<b>Audio</b>	Integrated Realtek High Definition Audio CODEC ALC892
<b>Operating Systems</b>	Windows 10 (64-bit) Windows 7 (32 and 64-bit) Windows Server 2012 R2 Ubuntu Linux Optional: QNX & embedded Please contact us directly for any special requirements
<b>Chassis Description</b>	Low Profile Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Input is 10V - 26VDC
<b>Power Input</b>	Rear 12VDC power Jack ideal for mobile applications Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz

<b>Power Management</b>	ACPI compliant and Operating System direct power management Wake-on event
<b>Hardware Monitor</b>	Processor temperature Cooling fan speed Voltage 100-240V AC Adapter
<b>Included with System</b>	North American Power Cord 4 Rubber Feet Wall Mount Bracket
<b>Options</b>	802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) WiFi and Bluetooth, Intel® AC7260 via internal Mini-PCIe Remote power option Ideal for OEM or Cabinet manufacturers Solid State Drives (SSD) SATA DisplayPort to VGA cable Custom Mounting Bracket Removable Computer Module on LCD Monitor 2 PS/2 ports for Keyboard & Mouse 2 x USB 3.0 Ports
<b>Rear Panel</b>	1x DVI-D video connector 1x DisplayPort video connector DC Power Input Jack 4 x 10/100/1000 RJ45 Network connections 3 x USB 2.0 Ports 2 x RS232 COM port
<b>Front Panel</b>	Headphone/Audio Line-Out Jack Microphone Input Jack Power and Hard Drive notification LED Power-on button
<b>Dimensions</b>	4.0"(W) x 6.1"(D) x 1.5"(H) (102mm x 155mm x 37.8mm) Operating Temperature: 0 - 40C (32 to 104 F)
<b>Environmental</b>	Storage Temperature: -20~60C (-4~140F) Operating Relative Humidity (non condensing) 10-80% Storage Relative Humidity (non condensing) 0-90% Power supply Weight: 1.35 lbs / 0.62 KG
<b>Weight</b>	Unit Weight: 1.3 lbs / 0.58 KG (Depending on configuration) Shipping Weight: 4 Lbs / 1.8 KG (Depending on configuration)
<b>Warranty</b>	1 Year limited Warranty Standard 1 Year Extended Warranty available (see Configurator/Price List)
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.