

## LPC-950 - RUGGED FANLESS, MINI PC WITH NVIDIA VIDEO



**\$3,995.00 USD**

### ***Powerful Fanless PC with Nvidia Video***

- Powerful Intel® Celeron®, 6th and 7th Generation Core™, & Xeon® processors
  - ECC Memory Support
- Dedicated NVIDIA® GeForce® Quadro T1000 graphics card
  - Supports up to 8K resolution, 7 Display support
- 32 DIO (16 In/16 Out Digital input/output) ports
  - Dual Removable Front Drives
  - Solid State Drives (SSD) Standard
  - PCIe x4 expansion slot
- Wide Range 10-36 VDC Input, ideal for mobile/field
  - Wall, VESA / DIN Rail mounting
  - Windows 10, Server 2022, and Linux
- RoHS, CE & FCC, EN50121-3-2, EN50155 certified
  - Wide Range Temperature version also available
  - Rackmount model version also available



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth LPC-950 Fanless Mini PC is the leading edge in small form factor computing. It features a dedicated NVIDIA® graphics card, along with Intel® 6th and 7th Generation Core™ i5, i7 & Xeon processors. Packed with robust capabilities, it is ideal for a large variety of demanding applications.

The LPC-950 Mini PC comes equipped with a dedicated NVIDIA® GeForce Quadro T1000 graphics card supporting up to 8K Resolution across 4 DisplayPort video ports. In combination with the Intel onboard video (DVI-D, VGA and 2 DisplayPort video ports), up to 7 displays can be connected simultaneously.

Fanless by design, the system operates without noisy cooling fans that can draw in dirt and dust causing potentially catastrophic failures. The space saving design features a rugged extruded aluminum chassis that provides superior heat dissipation.

The LPC-950 can be configured with 480GB to 16TB of total SSD storage (using dual drives), as well as 8GB to 64GB of RAM. ECC memory is available depending on the CPU selected. Also included are dual Removable Front Drive Bays that provide easy drive swapping and onboard Raid supporting 0/1 set-up options. The powerful small form factor PC includes an abundance of I/O ports such as USB 3.0, RS232 Serial, Gigabit networking, 32 DIO (Digital input/output), external SIM card sockets for wireless connectivity and audio/video ports.

Engineered to be extremely mobile friendly, the LPC-950 includes a Wide Range 10-36 VDC power input with a rear locking 3-Pin Ignition Switch. A TPM 2.0 (Trusted Platform Module) is incorporated to provide increased hardware security.

The LPC-900 series is RoHS, CE, FCC, EN50121-3-2 & EN50155 certified and designed for use in a multitude of applications including: Audio/Video Recording, Embedded Control, Digital Signs, Interactive Kiosks, IoT, Industrial Internet of Things (IIoT), Transportation, and Human/Machine Interface.

## ADDITIONAL INFORMATION

|                                  |                                                                                |
|----------------------------------|--------------------------------------------------------------------------------|
| <b>Processor</b>                 | Supporting Intel® Core™ 6th and 7th Generation, and Xeon® Processors           |
|                                  | Intel® Celeron® G3900TE (2 Cores / 2 Threads, 2.30Ghz)                         |
|                                  | Intel® Core™ i5-6500TE (4 Cores / 4 Threads, up to 3.30Ghz)                    |
|                                  | Intel® Core™ i7-6700TE (4 Cores / 8 Threads, up to 3.40Ghz)                    |
|                                  | Intel® Core™ i7-7700T (4 Cores / 8 Threads, up to 3.80Ghz)                     |
| <b>BIOS</b>                      | Intel® Xeon® E3-1268L v5 (4 Cores / 8 Threads, up to 3.40Ghz)                  |
|                                  | AMI                                                                            |
| <b>Chipset</b>                   | Intel® C236                                                                    |
| <b>Memory</b>                    | 2x DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory                   |
|                                  | Optional ECC Memory Support (available for Celeron and Xeon CPUs only)         |
| <b>Internal Storage</b>          | 256GB 3D NAND SSD (Solid State Drive) standard (SATA)                          |
|                                  | Options of up to 2TB SSD internal storage.                                     |
|                                  | Optional Onboard RAID configurations (0, 1), requires multiple drives          |
| <b>Internal Expansion Option</b> | (3) Full-Sized MiniPCIe Slots                                                  |
|                                  | PCIe x4 expansion slot (Up to 7" length)                                       |
|                                  | NVIDIA® GeForce® Quadro T1000 providing 4x DisplayPorts                        |
|                                  | Intel® HD Graphics 510 (Intel® Celeron)                                        |
|                                  | Intel® HD Graphics 530 (Intel® 6th Generation)                                 |
| <b>Video</b>                     | Intel® HD Graphics 630 (Intel® 7th Generation Processors)                      |
|                                  | Intel® HD Graphics P530 (Xeon)                                                 |
|                                  | Supports 8K UHD and 4K UHD Resolution as well as 1080p HD Video                |
|                                  | Up to 7 independent displays total (3 video ports using onboard Intel chipset) |
|                                  | Includes 1 VGA, 1 DVI and 6 DisplayPort video ports                            |
|                                  | - 1 VGA : Up to 1920 x 1200 @ 60Hz                                             |
|                                  | - 1 DVI : Up to 1920 x 1200 @ 60Hz                                             |
|                                  | - 2 DisplayPort : Up to 4096 x 2304 @ 60Hz                                     |
|                                  | - 4 DisplayPort : Up to 7680 x 3840 @ 60Hz                                     |

## Networking

LAN1: Intel® I219LM, LAN2: Intel® I210  
2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported  
Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe

## Communications

3x External SIM Card sockets for wireless connectivity

## Audio

Integrated Realtek High Definition Audio CODEC ALC892, 5.1 Channel HD Audio

## Operating Systems

Windows Server 2022  
Windows 10 (64-bit)  
Ubuntu Linux

## TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware security.

## Chassis Description

Fanless Rugged Aluminum Chassis

## Power Input

Input is 10V – 36V DC  
Rear Locking 3-Pin Ignition Switch (12V or 24V)  
Rear Locking 3-Pin power Jack ideal for mobile applications  
280W AC Adapter  
AC Adapter

## Included with System

North American Power Cord  
Wall Mount Bracket  
\* NOTE: Subject to change without notice  
10 – 36V DC Connector

## Rear Panel

1x Expansion Slot  
32 DIO (16 In/16 Out Digital input/output)  
4x DisplayPort Video connectors  
4x RS232 COM ports  
Rear Locking 3-Pin Ignition Switch (12V or 24V)  
2 x USB 3.0 Ports

## Front Panel

(2) Removable 2.5" Drive Bays  
1x Analog VGA / HD-15  
1x DVI-D video connector  
2x DisplayPort Video connectors  
2x Gigabit RJ45 Network connections  
3x SIM Card Communication Slots  
4x USB 3.0 Ports  
Audio Line-Out Jack  
Microphone Input Jack  
Power-on button  
Reset button

## Dimensions

10.2"(W) x 8.5"(D) x 3.1"(H) (260mm x 215mm x 79mm)  
Shock: IEC 60068-2-27, SSD: 50G @ wallmount, Half-sine, 11ms  
Storage Temperature: -10C – 60C (14F – 140F)

## Environmental

Vibration: IEC 60068-2-64, SSD: 5Grms, 5Hz to 500Hz, 3 Axis  
Humidity: 5% ~ 95%, non-condensing (Operating & Non-Operating)  
Operating Temperature: 0 – 40C (32 to 104 F)

## Approvals

EN50121-3-2  
EN50155  
RoHS  
CE  
FCC

## Weight

Unit Weight: 10.14 lbs / 4.6 KG (Depending on configuration)

## Warranty

2 Year limited Warranty, Standard  
1 Year Extended Warranty available (see Configurator/Price List)

## Disclaimer

Note: Specifications are subject to change without notice.