

## LPC-955 - RUGGED FANLESS, MINI PC WITH NVIDIA VIDEO (WIDE RANGE TEMPERATURE)



**\$3,995.00 USD**

### ***Wide Temperature Fanless PC with Nvidia Video***

- Powerful Intel® Celeron®, 6th and 7th Generation Core™, & Xeon® processors
  - ECC Memory Support
- Dedicated NVIDIA® GeForce® Quadro T1000 graphics card
  - Supports up to 8K resolution, 7 Display support
  - 32 DIO (16 In/16 Out Digital input/output) ports
  - Dual Removable Front Drives
- Wide Operating Temperature (-25°C - 60°C / -13°F - 140°F)
  - PCIe x4 expansion slot
- Wide Range 10-36 VDC Input, ideal for mobile/field
  - Wall, VESA / DIN Rail mounting
- Windows 7, 10, 10 IoT, Server 2022, and Linux
- RoHS, CE & FCC, EN50121-3-2, EN50155 certified
  - Rackmount model version also available



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth LPC-955 Wide Temperature Fanless Mini PC is the leading edge in small form factor computing. It features a dedicated NVIDIA® graphics card, along with Intel® 6th and 7th Generation Core™ i5, i7 & Xeon processors and supports operation in temperatures ranging from -25°C – 60°C.

Packed with robust capabilities, it is ideal for a large variety of demanding applications.

The LPC-955 Mini PC comes equipped with a dedicated NVIDIA® GeForce Quadro T1000 graphics card supporting up to 8K Resolution across 4 DisplayPort video ports. In combination with the Intel onboard video (DVI-D, VGA and 2 DisplayPort video ports), up to 7 displays can be connected simultaneously.

Fanless by design, the system operates without noisy cooling fans that can draw in dirt and dust causing potentially catastrophic failures. The space saving design features a rugged extruded aluminum chassis that provides superior heat dissipation.

The LPC-955 can be configured with 256GB to 4TB of total SSD storage (using dual drives), as well as 8GB to 64GB of RAM. ECC memory is available depending on the CPU selected. Also included are dual Removable Front Drive Bays that provide easy drive swapping and onboard Raid supporting 0/1 set-up options. The powerful small form factor PC includes an abundance of I/O ports such as USB 3.0, RS232

Serial, Gigabit networking, 32 DIO (Digital input/output), external SIM card sockets for wireless connectivity and audio/video ports.

Engineered to be extremely mobile friendly, the LPC-955 includes a Wide Range 10-36 VDC power input with a rear locking 3-Pin Ignition Switch. A TPM 2.0 (Trusted Platform Module) is incorporated to provide increased hardware security.

The LPC-900 series is RoHS, CE, FCC, EN50121-3-2 & EN50155 certified and designed for use in a multitude of applications including: Audio/Video Recording, Embedded Control, Digital Signs, Interactive Kiosks, IoT, Industrial Internet of Things (IIoT), Transportation, and Human/Machine Interface.

## ADDITIONAL INFORMATION

<b>Processor</b>	Supporting Intel® Core™ 6th and 7th Generation, and Xeon® Processors
	Intel® Celeron® G3900TE (2 Cores / 2 Threads, 2.30Ghz)
	Intel® Core™ i5-6500TE (4 Cores / 4 Threads, up to 3.30Ghz)
	Intel® Core™ i7-6700TE (4 Cores / 8 Threads, up to 3.40Ghz)
	Intel® Core™ i7-7700T (4 Cores / 8 Threads, up to 3.80Ghz)
<b>BIOS</b>	Intel® Xeon® E3-1268L v5 (4 Cores / 8 Threads, up to 3.40Ghz)
	AMI
<b>Chipset</b>	Intel® C236
<b>Memory</b>	2x DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory
	Optional ECC Memory Support (available for Celeron and Xeon CPUs only)
<b>Internal Storage</b>	256GB TLC SSD (Solid State Drive) Wide Temp standard (SATA)
	Options of up to 2TB SSD internal storage.
<b>Internal Expansion Option</b>	Optional Onboard RAID configurations (0, 1), requires multiple drives
	(3) Full-Sized MiniPCIe Slots
	PCIe x4 expansion slot (Up to 7" length)
	NVIDIA® GeForce® 1050Ti or Quadro T1000 providing 4x DisplayPorts
	Intel® HD Graphics 510 (Intel® Celeron)
<b>Video</b>	Intel® HD Graphics 530 (Intel® 6th Generation)
	Intel® HD Graphics 630 (Intel® 7th Generation Processors)
	Intel® HD Graphics P530 (Xeon)
	Supports 8K UHD and 4K UHD Resolution as well as 1080p HD Video
	Up to 7 independent displays total (3 video ports using onboard Intel chipset)
	Includes 1 VGA, 1 DVI and 6 DisplayPort video ports
	– 1 VGA : Up to 1920 x 1200 @ 60Hz
	– 1 DVI : Up to 1920 x 1200 @ 60Hz
	– 2 DisplayPort : Up to 4096 x 2304 @ 60Hz
	– 4 DisplayPort : Up to 7680 x 3840 @ 60Hz

## Networking

LAN1: Intel® I219LM, LAN2: Intel® I210  
2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported  
Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe

## Communications

3x External SIM Card sockets for wireless connectivity

## Audio

Integrated Realtek High Definition Audio CODEC ALC892, 5.1 Channel HD Audio

## Operating Systems

Windows Server 2022  
Windows 10 (64-bit)  
Windows 10 IoT Enterprise  
Ubuntu Linux

## TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware security.

## Chassis Description

Fanless Rugged Aluminum Chassis

## Power Input

Input is 10V - 36V DC  
Rear Locking 3-Pin Ignition Switch (12V or 24V)  
Rear Locking 3-Pin power Jack ideal for mobile applications  
280W AC Adapter

## Included with System

AC Adapter  
North American Power Cord  
Wall Mount Bracket  
\* NOTE: Subject to change without notice  
10 - 36V DC Connector

## Rear Panel

1x Expansion Slot  
32 DIO (16 In/16 Out Digital input/output)  
4x DisplayPort Video connectors  
4x RS232 COM ports  
Rear Locking 3-Pin Ignition Switch (12V or 24V)  
2 x USB 3.0 Ports

Front Panel	(2) Removable 2.5" Drive Bays
	1 x CFast Socket with Push-in/Pull-out Ejector
	1x Analog VGA / HD-15
	1x DVI-D video connector
	2x DisplayPort Video connectors
	2x Gigabit RJ45 Network connections
	3x SIM Card Communication Slots
	4x USB 3.0 Ports
	Audio Line-Out Jack
	Microphone Input Jack
Dimensions	Power-on button
	Reset button
	10.2"(W) x 8.5"(D) x 3.1"(H) (260mm x 215mm x 79mm)
Environmental	Operating Temperature: -25°C – 60°C (-13°F – 140°F)
	Storage Temp: -40°C to 85°C (-40°F to 185°F)
	Shock: IEC 60068-2-27, SSD: 50G @ wallmount, Half-sine, 11ms
	Vibration: IEC 60068-2-64, SSD: 5Grms, 5Hz to 500Hz, 3 Axis
	Humidity: 5% ~ 95%, non-condensing (Operating & Non-Operating)
Approvals	EN50121-3-2
	EN50155
	RoHS
	CE
Weight	FCC
	Unit Weight: 10.14 lbs / 4.6 KG (Depending on configuration)
Warranty	2 Year limited Warranty, Standard
	1 Year Extended Warranty available (see Configurator/Price List)
Disclaimer	Note: Specifications are subject to change without notice.