

## LPC-100 - ULTRA SMALL MINI PC



### ***Our Smallest Full Featured Mini PC Ever!***

- Ultra Small, Only 4.0" x 6.1" x 1.45" in size
  - Powerful Intel Mobile Processors
  - 12 VDC Operation, Ideal for Mobile/Field
    - Up to 1TB Internal Storage
    - SSD (Solid State Drive) Optional
- Built-in GB LAN, USB 2.0, Audio, Serial, Video
  - Low Profile Rugged Aluminium Chassis
  - Panel/Wall Mount Brackets Included
  - Mountable to our LCD Monitors
- Windows 7, 8, 8.1 Compatible, \*other O/S Options Available

***(Important Notice: The LPC-100 model is now end of life and is replaced by the functional equivalent model LPC-140G4.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Simply amazing! - The most processing power in the smallest package Stealth has ever produced. Utilizing Intel's Mobile Core 2 Duo Processors the LPC-100 delivers the ultimate in small form factor performance. The LPC-100 Mini PC is an excellent choice for industrial and commercial applications which include, Embedded Control, Digital Signs, Interactive Kiosks, Thin-Clients, and Human/Machine Interface applications.

Barely larger than a deck of playing cards (4.0" x 6.1" x 1.45") the LPC-100 ultra Mini PC provides CPU performance, I/O connectivity, graphics performance and hard drive space typically found in large PC systems. The LPC-100 operates from an external 12VDC power adapter (included) or can be connected to an external DC source making it ideal for mobile and remote applications.

## ADDITIONAL INFORMATION

<b>Processor</b>	Supports Intel's Dual Core Processors. Offered with Intel's Core 2 Duo P8400 (2.26Ghz) (Standard)
<b>Chipset</b>	Intel's GM45 Chipset with Intel's ICH9M Winbond W83627EHG
<b>BIOS</b>	Award PnP Flash BIOS
<b>Memory</b>	Offers 2 x DDR3 SO-Dimm memory slots providing options up to 8GB of RAM
<b>Internal Storage</b>	Offered with 500GB Serial ATA (SATA) with options of up to 1TB capacity
<b>Internal Expansion Option</b>	1 Internal Mini-PCle expansion option 1 External ExpressCard/34 slot (34mm wide) PCle and USB devices supported
<b>Video</b>	Onboard Intel Graphics Media Accelerator 4500MHD Shared 128MB Video Memory with DVMT Includes DVI-I with DVI to VGA adapter and DVI-D via Adapter (Digital Only) Optional Video Splitter cable for DVI-I to DVI-D and VGA Dual Display support (clone or extended desktop)
<b>Networking</b>	Integrated 10/100/1000 Base-T Intel Pro 1000 PL (82573L) Gigabit Ethernet controller, RJ45 connection (PXE support)
<b>Audio</b>	Integrated Realtek High Definition Audio CODEC ALC888
<b>Operating Systems</b>	Windows 7 (32 and 64-bit) Windows XP (32-Bit and 64-Bit) Windows Server 2008 Ubuntu Linux Optional: QNX & embedded Please contact us directly for any special requirements
<b>Chassis Description</b>	Low Profile Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Rear 12VDC power Jack ideal for mobile applications Input is 12VDC +/-5%
<b>Power Input</b>	Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz 12VDC output, 7A MAX (84W)

## Power Consumption

Power off state: (1.7W)\*

Initial Start-up / Power Up Peek: (33W)\*

Windows Idle: (15W)\* Full Load: (31W)\*

\*Based on T3100 CPU, 160GB HDD and 4GB RAM under Windows XP

## Power Management

ACPI 3.0 compliant OS Direct power management

Wake-on event

## Hardware Monitor

Processor temperature

Cooling fan speed

Voltage

## Included with System

LPC-100-WM-BRACKET, Mounting Bracket

100-240V AC Adapter

North American Power Cord

DVI to VGA Adapter

4 Rubber Feet

## Options

Remote power option Ideal for OEM or Cabinet manufacturers

Solid State Drives (SSD) SATA

Custom Mounting Bracket

Removable Computer Module on LCD Monitor

2 PS/2 ports for Keyboard & Mouse

1x Gigabit RJ45 Network connection

## Rear Panel

1 x USB 2.0 Port

1x DVI-I video connector

12VDC Power Input Jack

2 x USB 2.0 Ports

2 x RS232 COM port

## Front Panel

Headphone/Audio Line-Out Jack

Microphone Input Jack

Power and Hard Drive notification LED

Power-on button

## Dimensions

4.0"(W) x 6.1"(D) x 1.45"(H) (102mm x 155mm x 37mm)

## Environmental

Operating Temperature: 0 - 40C (32 to 104 F)

Storage Temperature: -20~60C (-4~140F)

Operating Relative Humidity (non condensing) 10-80%

Storage Relative Humidity (non condensing) 0-90%

## Approvals

RoHS

CE

## Weight

Power supply Weight: 1.35 lbs / 0.62 KG

Unit Weight: 1.2 lbs / 0.54 KG (Depending on configuration)

Shipping Weight: 4 Lbs / 1.8 KG (Depending on configuration)

## **Warranty**

1 Year limited Warranty Standard

1 Year Extended Warranty available (see Configurator/Price List)

## **Disclaimer**

Note: Specifications are subject to change without notice.