

LPC-140G4 - ULTRA SMALL MINI PC - CELERON CPU, 16GB, 480GB SSD, WIN 10 (QUICKSHIP SPECIAL)



\$1,580.00 USD Original price was: \$1,580.00 USD.<u>\$1,185.00 USD</u>Current price is: \$1,185.00 USD.

4-Gigabit Ethernet Ports in the palm of your hand!

- 4 Gigabit Ethernet LAN/WAN ports
- Ultra Small, Only 4.0" x 6.1" x 1.5" in size
- Intel® Celeron® Dual Core 2980U, 1.6Ghz Processor
 - 16GB DDR3 Memory
 - 480GB SSD (Solid State Drive)
 - 4 Gigabit Ethernet LAN/WAN ports
 - 10-26 VDC Operation, Ideal for Mobile/Field
 - Includes AC Power Adapter
 - Built-in GB LAN, USB 3.0/2.0, Audio, Serial, Video
 - Windows 10 Professional, OEM
 - Panel/Wall Mount Brackets Included
 - 6-Month Warranty

25% Off









GALLERY IMAGES





PRODUCT DESCRIPTION

The Stealth LPC-140G4 Multi-LAN Ultra Small Mini PC features a total of 4 GB Ethernet ports all in one tiny machine measuring (4.0" x 6.1" x 1.45") or just a little larger then a deck of playing cards.

The LPC-140G4 is a powerful, feature rich small-form PC that harnesses the power Intel's 4th generation i3 and Celeron mobile processors. Ideal applications include; security, VPN, network appliance, bandwidth controller, network diagnostics, IoT (Internet of Things), mini servers and more.

The LPC-140G4 operates from an external AC power adapter (included) or can be connected to an external 10-26 VDC source making it ideal for mobile and remote applications.

Stealth's LittlePCs are small form factor mini PCs designed to fit in space-confined areas and are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Transportation, mining and Telecommunications markets.



ADDITIONAL INFORMATION

Processor	Intel [®] Celeron [®] Dual Core 2980U, 1.6Ghz, 32/64-Bit
Chipset	8-series chipset integrated in CPU
BIOS	Insyde UEFI BIOS
Memory	16GB DDR3 Memory
Internal Storage	480GB SSD 3D Nand Drive
Internal Expansion Option	1 Internal Mini-PCIe expansion option PCIe and USB devices supported
Video	Onboard/Integrated Intel HD Graphics (built into the CPU) Dual Display support (clone or extended desktop)
Networking	3x Integrated 10/100/1000 Base-T Intel (i210-AT) Gigabit Ethernet controller, RJ45 connection (PXE support) 1x Integrated 10/100/1000 Base-T Intel (i218LM) Gigabit Ethernet controller, RJ45 connection (PXE support)
Audio	Integrated Realtek High Definition Audio CODEC ALC892
Operating Systems	Windows 10 (64-bit)
Operating Systems Chassis Description	Low Profile Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets
	Low Profile Rugged Aluminum Chassis
Chassis Description	Low Profile Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Input is 10V – 26VDC Rear 12VDC power Jack ideal for mobile applications Includes External AC Adapter, Input 100~240V AC @ 1.5A
Chassis Description Power Input	Low Profile Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Input is 10V – 26VDC Rear 12VDC power Jack ideal for mobile applications Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz ACPI compliant and Operating System direct power management

STEALTH

Rear Panel	2 PS/2 ports for Keyboard & Mouse 2 x USB 3.0 Ports 1x DVI-D video connector 1x DisplayPort video connector DC Power Input Jack
Front Panel	4 x 10/100/1000 RJ45 Network connections 3 x USB 2.0 Ports 2 x RS232 COM port Headphone/Audio Line-Out Jack Microphone Input Jack Power and Hard Drive notification LED Power-on button
Dimensions	4.0"(W) x 6.1"(D) x 1.5"(H) (102mm x 155mm x 37.8mm)
Environmental	Operating Temperature: 0 – 40C (32 to 104 F) Storage Temperature: -20~60C (-4~140F) Operating Relative Humidity (non condensing) 10-80% Storage Relative Humidity (non condensing) 0-90%
Weight	Power supply Weight: 1.35 lbs / 0.62 KG Unit Weight: 1.3 lbs / 0.58 KG (Depending on configuration) Shipping Weight: 4 Lbs / 1.8 KG (Depending on configuration)
Warranty	6-Months Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.