

WPC-905 - HIGH PERFORMANCE RUGGED FANLESS WATERPROOF PC



\$2,875.00 USD

A Completely Sealed Mobile PC for Harsh Environment and Marine Applications

- Waterproof / Water Resistant
 - Dust, rain and splash resistant, Sealed to IP67 specifications
 - Fanless Noise Free, Low Power Consumption
- Powerful 8th Generation Intel® Celeron®, and Core™ Processors
 - DC Input, Wide Range 9 - 48VDC
- Solid State Hard Drives (SSD) with optional RAID configurations
 - Small Form Factor design
 - Windows 10, Server 2019, and Linux compatible
- RoHS, CE & FCC, EN50121-3-2, EN50155 certified



GALLERY IMAGES



PRODUCT DESCRIPTION

The new Stealth WPC-905 is a high performance rugged Waterproof PC computer that is completely sealed, surviving liquids, chemicals, dust and dirt intrusion and meeting IP67/NEMA 6 environmental specifications. Designed without cooling fans the rugged chassis acts as a heat sink to dissipate internal heat and provide noise free operation.

This durable environmentally sealed small form PC features powerful 8th Generation Intel® Celeron®, and Core™ Processors, solid state drives (SSD) with optional onboard RAID configurations and operates from a wide range of DC input power (9 - 48VDC) making it a perfect fit for mobile and transportation based applications.

The WPC-905 is RoHS, CE & FCC, EN50121-3-2, EN50155 certified and also incorporates TPM 2.0 (Trusted Platform Module) to provide increased hardware security.

Stealth's Waterproof PC products are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Marine, IoT, Industrial Internet of Things (IIoT), Transportation, Mining and Telecommunications markets.

ADDITIONAL INFORMATION

Processor

Supporting Intel®'s 8th Generation Core™ Processors
Intel® Celeron® 4305UE (2 Cores / 2 Threads, 2.00 GHz)
Intel® Core™ i3-8145UE (2 Cores / 4 Threads, up to 3.90 GHz)
Intel® Core™ i5-8365UE (4 Cores / 8 Threads, up to 4.10 GHz)
Intel® Core™ i7-8665UE (4 Cores / 8 Threads, up to 4.40 GHz)

Chipset

Intel® SoC (Cannon Lake)

Memory

(1) DDR4 SO-DIMM Memory Slot, up to 32GB

Internal Storage

Options of up to 2TB SSD internal storage.
2 x 2.5" Internal Drive bays
Optional Onboard RAID configurations (0, 1), requires multiple drives
Optional (1) mSATA drive support

Internal Expansion Option

1 Full size Mini-PCIe slot, supports PCIe, mSATA and USB interface

Video

Intel® UHD Graphics 620 (Intel® 8th Generation Processors)
Intel® HD Graphics 610 (Intel® Celeron and Pentium Processors)
DVI-D max. resolution 1920 x 1200 @ 60 Hz

Networking

Intel® iAMT 11.0 Supported (LAN 1)
M12 Connector, X-coded
LAN1: Intel® I219LM, LAN2: Intel® I210
PXE (Pre-Boot Execution Environment) Support
WoL (Wake On Lan) Support

Audio

No Audio Support

TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware security.

Operating Systems

Windows 11 (64-bit)
Windows 10 (64-bit)
Windows Server 2019
Ubuntu Linux
Please contact us directly for any special requirements

Chassis Description

Rugged Aluminum Chassis
Vesa 75mm/100mm Mounting on bottom
Completely Sealed Water, dust & debris Proof enclosure
Fanless Design
Fully IP67/NEMA 6 rated, Highest level for Dust and Water Proof

Power Input

M12 Connector, A-coded
Input is 9V – 48V DC

Hardware Monitor

Processor temperature
System temperature
Voltage

Rear Panel

(1) DVI-D IP67 Connector
(1) Power input port, M12, A-Coded
(1) RS-232 Serial Port, M12, A-Coded
(2) 2-port USB 2.0 ports, M12, A-Coded
(2) Network ports, M12, X-Coded
(6) Water tight M12 Connectors

Front Panel

Power and Hard Drive notification LED
Power-on button

Dimensions

9.8" x 7.1" x 1.7" (250mm x 180mm x 44mm) [W x D x H]

Environmental

Operating Temp: -30°C to 70°C (-22°F to 158°F)
Relative Humidity: 95% @ 70°C
Storage Temp: -40°C to 85°C (-40°F to 185°F)
Humidity: 5% ~ 95%, non-condensing (Operating & Non-Operating)

Approvals

EN50121-3-2
EN50155
RoHS
CE
FCC

Shock

Operating: 15g/11ms, ½ sine, 3 shocks in +ve and -ve direction, all 3 axes (IEC 60068-2-27)
Storage: 50g/11ms, ½ sine, 3 shocks in +ve and -ve direction, all 3 axes (IEC 60068-2-27)

Weight

Unit Weight (w/o cables): 5.1 lbs. / 2.32kgs.

Warranty

2 Year limited Warranty, Standard
1 Year Extended Warranty available (see Configurator/Price List)

Included with System

Includes (1) Watertight DVI cable
Includes set of (6) watertight cables with mating M12 connectors
100-240V AC Adapter
North American Power Cord
Wall Mount Bracket

Disclaimer

Note: Specifications are subject to change without notice.