

LPC-140G4FS - ULTRA SMALL FANLESS MINI PC - 16GB, 480GB SSD, WIN 10 (QUICKSHIP SPECIAL)



~~\$1,685.00 USD~~ Original price was:
~~\$1,685.00 USD.~~ ~~\$1,263.00 USD~~ Current price is:
\$1,263.00 USD.



Fanless, Ultra Small Form Factor PC

- Fanless, No Noise, Silent Operation
- Ultra Small, Only 2.0"(H) x 5.79" (D) x 4.6" (W) in size
- Intel® Celeron® Dual Core 2980U, 1.6Ghz Processor
 - 16GB DDR3 Memory
 - 480GB SSD (Solid State Drive)
 - 4 Gigabit Ethernet LAN/WAN ports
- 10-26 VDC Operation, Ideal for Mobile/Field
 - Includes AC Power Adapter
- Built-in GB LAN, USB 3.0/2.0, Audio, Serial, Video
 - Windows 10 Professional, OEM
 - Panel/Wall Mount Brackets Included
 - 6-Month Warranty
- See our FAQ – Why Choose Fanless?

25% Off



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth LPC-140G4FS is a Fanless Ultra Small Mini PC which features a total of 4 GB Ethernet ports all in small form factor chassis measuring only (4.6" x 6.1" x 2.0") in size.

The Fanless Computer is a powerful, feature rich small-form PC that harnesses the power Intel's 4th generation Haswell ULT Celeron processor. Ideal applications include; security, VPN, network appliance, bandwidth controller, network diagnostics, IoT (Internet of Things), IIoT (Industrial Internet of Things), M2M (Machine-to-Machine), mini servers and more.

Fanless by design, Stealth's LPC-140G4FS operates without the use of noisy cooling fans. Typical PC cooling fans can draw in dirt and dust from their operating environments potentially causing catastrophic failures or unplanned downtime. See our [Fanless Computing FAQ - Why Choose Fanless?](#)

The LPC-140G4FS operates from an external AC power adapter (included) or can be connected to an external 10-26 VDC source making it ideal for mobile and remote applications.

Stealth's LittlePCs are small form factor mini PCs designed to fit in space-confined areas and are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Transportation, Mining and Telecommunications markets.

ADDITIONAL INFORMATION

Processor	Intel® Celeron® Dual Core 2980U, 1.6Ghz, 32/64-Bit
Chipset	8-series chipset integrated in CPU
BIOS	Insyde UEFI BIOS
Memory	16GB DDR3 Memory
Internal Storage	480GB SSD 3D Nand Drive
Internal Expansion Option	1 Internal Mini-PCle expansion option PCIe and USB devices supported
Video	Onboard/Integrated Intel HD Graphics (built into the CPU) Dual Display support (clone or extended desktop) 3x Integrated 10/100/1000 Base-T Intel (i210-AT) Gigabit Ethernet controller, RJ45 connection (PXE support)
Networking	1x Integrated 10/100/1000 Base-T Intel (i218LM) Gigabit Ethernet controller, RJ45 connection (PXE support)
Audio	Integrated Realtek High Definition Audio CODEC ALC892
Operating Systems	Windows 10 (64-bit)
Chassis Description	Fanless Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Input is 10V - 26VDC
Power Input	Rear 12VDC power Jack ideal for mobile applications Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz
Power Management	ACPI compliant and Operating System direct power management Wake-on event
Hardware Monitor	Processor temperature Cooling fan speed Voltage
Included with System	100-240V AC Adapter North American Power Cord 4 Rubber Feet Wall Mount Bracket

Rear Panel

2 PS/2 ports for Keyboard & Mouse
2 x USB 3.0 Ports
1x DVI-D video connector
1x DisplayPort video connector
DC Power Input Jack
4 x 10/100/1000 RJ45 Network connections
3 x USB 2.0 Ports
2 x RS232 COM port

Front Panel

Headphone/Audio Line-Out Jack
Microphone Input Jack
Power and Hard Drive notification LED
Power-on button

Dimensions

4.6"(W) x 6.1"(D) x 2.0"(H) (117mm x 155mm x 52mm)

Environmental

Operating Temperature: 0 - 40C (32 to 104 F)
Storage Temperature: -20~60C (-4~140F)
Operating Relative Humidity (non condensing) 10-80%
Storage Relative Humidity (non condensing) 0-90%

Weight

Power supply Weight: 1.35 lbs / 0.62 KG
Unit Weight: 1.3 lbs / 0.58 KG (Depending on configuration)
Shipping Weight: 4 Lbs / 1.8 KG (Depending on configuration)

Warranty

6-Months Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.