

## LPC-140G4FS - ULTRA SMALL FANLESS MINI PC WITH 4 GIGABIT LAN PORTS



**\$1,300.00 USD**



### ***Fanless, Ultra Small Form Factor PC***

- Fanless, No Noise, Silent Operation
- Ultra Small, Only 2.0"(H) x 5.79" (D) x 4.6" (W) in size
  - 10-26 VDC Operation, Ideal for Mobile/Field
    - 4 Gigabit Ethernet LAN/WAN ports
    - Up to 2TB Internal Storage
    - SSD (Solid State Drive) Standard
- Built-in GB LAN, USB 3.0/2.0, Audio, Serial, Video
  - Panel/Wall Mount Brackets Included
  - See our FAQ - Why Choose Fanless?

**The LPC-140G4FS model is now end of life with limited stock remaining. Please contact us for availability or replacement options.**



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth LPC-140G4FS is a Fanless Ultra Small Mini PC which features a total of 4 GB Ethernet ports all in small form factor chassis measuring only (4.6" x 6.1" x 2.0") in size.

The Fanless Computer is a powerful, feature rich small-form PC that harnesses the power Intel's 4th generation Haswell ULT Celeron processor. Ideal applications include; security, VPN, network appliance, bandwidth controller, network diagnostics, IoT (Internet of Things), IIoT (Industrial Internet of Things), M2M (Machine-to-Machine), mini servers and more.

Fanless by design, Stealth's LPC-140G4FS operates without the use of noisy cooling fans. Typical PC cooling fans can draw in dirt and dust from their operating environments potentially causing catastrophic failures or unplanned downtime. See our [Fanless Computing FAQ - Why Choose Fanless?](#)

The LPC-140G4FS operates from an external AC power adapter (included) or can be connected to an external 10-26 VDC source making it ideal for mobile and remote applications.

Stealth's LittlePCs are small form factor mini PCs designed to fit in space-confined areas and are ideal for demanding applications within the Industrial, Commercial, Scientific Research, Military, Public Safety, Utility, Transportation, Mining and Telecommunications markets.

## ADDITIONAL INFORMATION

<b>Processor</b>	Intel® Celeron® Dual Core 2980U, 1.6Ghz, 32/64-Bit
<b>Chipset</b>	8-series chipset integrated in CPU
<b>BIOS</b>	Insyde UEFI BIOS
<b>Memory</b>	Offers 2 x DDR3 SO-Dimm memory slots providing options up to 16GB of RAM
<b>Internal Storage</b>	256GB 3D NAND SSD (Solid State Drive) standard (SATA) Options of up to 2TB SSD internal storage.
<b>Internal Expansion Option</b>	1 Internal Mini-PCIe expansion option PCIe and USB devices supported
<b>Video</b>	Onboard/Integrated Intel HD Graphics (built into the CPU) Dual Display support (clone or extended desktop) 3x Integrated 10/100/1000 Base-T Intel (i210-AT) Gigabit Ethernet controller, RJ45 connection (PXE support) 1x Integrated 10/100/1000 Base-T Intel (i218LM) Gigabit Ethernet controller, RJ45 connection (PXE support)
<b>Networking</b>	Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe
<b>Audio</b>	Integrated Realtek High Definition Audio CODEC ALC892
<b>Operating Systems</b>	Windows 10 (64-bit) Windows 7 (32 and 64-bit) Windows Server 2016 Ubuntu Linux Please contact us directly for any special requirements
<b>Chassis Description</b>	Fanless Rugged Aluminum Chassis Includes Panel/Wall Mount Brackets Input is 10V - 26VDC
<b>Power Input</b>	Rear 12VDC power Jack ideal for mobile applications Includes External AC Adapter, Input 100~240V AC @ 1.5A 50-60Hz
<b>Power Management</b>	ACPI compliant and Operating System direct power management Wake-on event

**Hardware Monitor**

Processor temperature

Cooling fan speed

Voltage

**Included with System**

100-240V AC Adapter

North American Power Cord

4 Rubber Feet

Wall Mount Bracket

802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) WiFi and Bluetooth,  
Intel® AC7260 via internal Mini-PCIe

Remote power option Ideal for OEM or Cabinet manufacturers

**Options**

Solid State Drives (SSD) SATA

DisplayPort to VGA cable

Custom Mounting Bracket

Removable Computer Module on LCD Monitor

2 PS/2 ports for Keyboard &amp; Mouse

2 x USB 3.0 Ports

**Rear Panel**

1x DVI-D video connector

1x DisplayPort video connector

DC Power Input Jack

4 x 10/100/1000 RJ45 Network connections

3 x USB 2.0 Ports

2 x RS232 COM port

**Front Panel**

Headphone/Audio Line-Out Jack

Microphone Input Jack

Power and Hard Drive notification LED

Power-on button

**Dimensions**

4.6"(W) x 6.1"(D) x 2.0"(H) (117mm x 155mm x 52mm)

Operating Temperature: 0 - 40C (32 to 104 F)

Storage Temperature: -20~60C (-4~140F)

**Environmental**

Operating Relative Humidity (non condensing) 10-80%

Storage Relative Humidity (non condensing) 0-90%

Power supply Weight: 1.35 lbs / 0.62 KG

**Weight**

Unit Weight: 1.3 lbs / 0.58 KG (Depending on configuration)

Shipping Weight: 4 Lbs / 1.8 KG (Depending on configuration)

**Warranty**

1 Year limited Warranty Standard

1 Year Extended Warranty available (see Configurator/Price List)

**Disclaimer**

Note: Specifications are subject to change without notice.