

17" PANEL MOUNT LCD MONITOR (QUICKSHIP)





\$1,285.00 USD

Model: SV-1701-PM

- Panel Mount LCD, 17" Industrial Grade
 - NEMA 4/IP65 Environmentally Sealed
- Touch Screen Standard (Capacitive or Resistive)
 - Wide Viewing Angles
- 250 Nits of Brightness, Adjustable Controls
- Stainless Steel (NEMA 4X) & Custom painted bezel options
 - VGA & DVI-D video connectors
 - cULus Listed
 - 2 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth builds high quality LCD monitors suited for industrial and commercial applications. Our 17" Panel Mount LCD Monitor comes equipped with an environmentally sealed front panel that is resistant to splashes or hose downs. All Stealth Panel Mount LCD products are easily installed by securing the rear studs into your console, panel or wall.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

We offer Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Stealth's LCD products are environmentally sealed to NEMA 4 / IP65 and are ideal for applications where dirt, dust, moisture and water are present.

Stealth's rugged LCD products are constructed from solid steel and stainless steel for corrosion resistance applications. Our LCDs are available with various Touch Screen options including Resistive or Capacitive. For non-touch applications our anti-glare protective glass overlay is installed for maximum protection.

ADDITIONAL INFORMATION

Bezel Type	Panel Mount
Screen Size	17.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.264mm x 0.264mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	170° (H) / 160° (V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical) SmartContrast: 20,000,000:1
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 13.39" / 340.1 mm, Vertical: 10.71" / 272.03 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync Sync on Green
Input	AC Input: 100-240V, 50-60Hz, 1.5A
Control Buttons (Rear mounted)	Smart Image, Down, Up, Menu/OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out

Environmental Rating

Standard Bezel: NEMA 4 / IP65 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water

Optional Stainless Steel Bezel: NEMA 4X / IP65 Front Panel (when properly installed) corrosion protection, protection against windblown dust and rain, splashing water, and hose-directed water

Environmental

Operating Temperature: 0 – 40C (32 to 104 F)

Storage Temperature: -20~60C (-4~140F)

Operating: Relative Humidity 20% ~ 80%

Storage Relative Humidity: 20% ~ 80%

Approvals

cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07

Panel Finish

Black Baked Enamel (Standard)

Stainless Steel – Brushed #304 (Optional)

Unit Weight

Unit Weight: 14.9 Lbs (6.76 Kg)*

Shipping Weight: 21.2 Lbs (9.62 Kg)*

* Weight may vary depending on configuration

Dimensions

Panel Mount: 18.9"(W) x 17.0"(H) x 2.5"(D) 480.06mm x 431.8mm x 63.68mm

Available Models

SV-1701-PM-RT – Standard Bezel (NEMA 4), Resistive Touch with Serial/DB9 and USB Interface

Warranty

2 Year Parts & Labor

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.