

24" PANEL MOUNT LCD MONITOR (SV-2410W-PM) (QUICKSHIP)



\$1,905.00 USD

Model: SV-2410W-PM

- Panel Mount 24" Widescreen LCD Monitor
 - NEMA 4/IP65 Environmentally Sealed
- Resistive Touch Screen Standard (Optional Capacitive)
 - 16:10 Aspect Ratio
 - 1920 x 1200 Maximum Resolution
- 300 Nits of Brightness, Adjustable Controls
- VGA, DVI-D, Displayport & HDMI connectors
 - Wide Viewing Angles, 178°
- Stainless Steel & Custom painted bezel options
 - cULus Listed
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 24" Panel Mount LCD monitor features a widescreen 16:10 high resolution display that easily integrates into your enclosure, cabinet, console, wall, kiosks or other industrial applications. Mounting the display is accomplished by simply securing the rear metal studs into your application cutout.

All Stealth Panel Mount LCD products come standard with an environmentally sealed NEMA 4, 4X / IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. The rugged SV-2410W-PM LCD is available with a capacitive or a resistive touchscreen.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our Rugged LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

| | |
|---------------------------------------|---|
| Bezel Type | Panel Mount |
| Screen Size | 24.0" (Diagonal) |
| Aspect Ratio | 16:10 |
| Native Resolution | 1920 x 1200 (Auto sync from 640 x 480 to 1920 x 1200) |
| Horizontal Frequency | 31.5KHz – 95KHz |
| Vertical Frequency | 56 Hz ~ 75 Hz |
| Pixel Pitch | 0.27mm x 0.27mm |
| Response Time | 5ms Typical |
| Type | IPS LCD Panel c/w LED Backlighting VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI Displayport DisplayPort Multi-Stream Transport (MST) port (Clone or Extended Desktop) |
| Video Input Connectors | |
| Viewing Angle | 178° / 178° (H / V) – (Viewing angle of LCD panel sans touch) |
| Contrast Ratio | 1000:1 (typical) |
| Luminance (Brightness) | 300 cd/m2 typical at center (300 Nits) |
| Viewable Image Size | Horizontal: 20.41" (518.4mm) Vertical: 12.76" (324.0mm) |
| Video Signal | ANALOG: 0.7 Vp-p/75 Ohms Separate Sync |
| Sync Signal | Sync on Green Composite Sync |
| Input | AC Input: 120 – 240VAC ~ 60/50 Hz Power Consumption: 29 W (typical) |
| Control Buttons (Rear mounted) | Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF |

Controls On-Screen Display

Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out

Environmental Rating

Standard Bezel: NEMA 4 / IP65 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water

Environmental

Operating Altitude: 0 - 16,404 feet (0 - 5000m)

Operating Humidity: 20% - 80%

Operating Temperature: 5C - 35C (41F - 95F)

Storage Altitude: 0 - 40,000 Feet (0 - 12,192m)

Storage Humidity: 10% - 85%

Storage Temperature: -10C - 60C (14F - 140F)

Panel Finish

Black Baked Enamel (Standard)

Stainless Steel - Brushed #304 (Optional)

Unit Weight

20 Pounds (9.07Kg)

Dimensions

Panel Mount: 24.5"(W) x 16.75"(H) x 2.8"(D) 622.3mm x 425.5mm x 71.1mm

Available Models

SV-2410W-PM-CT-USB - Capacitive (USB)

SV-2410W-PM-RT - Resistive (USB and Serial / DB9)

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.