

LPC-490F - FANLESS - CELERON® G4900T, 16GB, 480GB SSD, DVDRW, WIN 10 (QUICKSHIP)



\$1,880.00 USD

Featuring a high performance Small PC with abundant network connectivity

- Intel® Celeron® G4900T (2 Cores / 2 Threads, up to 2.9Ghz), Fanless
 - 16GB DDR4 Memory
 - DVDRW Optical Drive
 - 480GB Solid State Hard Drives (SSD)
 - Windows 10 Professional 64-Bit
 - 10-48 VDC Operation, ideal for mobile/field
 - Includes 3-Pin locking power connector and

mobile hardware start-up and shutdown features

• Built-in 4 Gigabit LAN, 4 USB 3.0, Audio, Serial, Video



Page: 1 April 25, 2024



GALLERY IMAGES







PRODUCT DESCRIPTION

The LPC-490F is a high performance Fanless Mini PC featuring a multitude of I/O including 4 RJ45 Gigabit LAN ports, DVI-I and DisplayPort video ports. It is offered with a choice of Intel® Coffee Lake 8th Generation Celeron or Pentium Gold Processors. All this power is packed into one tiny machine that is small enough to fit on the palm of your hand!

The LPC-490F Little PC is packed with features including a wide DC input range of 10-48V, a locking 3-Pin Power Jack, voltage power on sense (ideal for mobile applications), up to 3 Drives in a combination of M.2 NVMe[™], 2.5" Hard Drives or Solid State Drives with optional onboard Raid support, an optional front slot loading Optical Drive or removable drive, up to 64GB memory, onboard audio, and much more.

Typical applications include:

- Instrumentation and Control
 - Security
 - Mobile & Vehicle PC
 - VPN
 - Network Appliance
 - Kiosk
 - Data acquisition
 - IoT (Internet of Things)
 - Mini Servers

The LPC-490 series adds to Stealth's robust lineup of Small Form Factor Mini PCs designed to fit in spaceconfined areas and are ideal for demanding applications within the Industrial, Commercial, Military & Defense, Scientific Research, Public Safety, Utility, Transportation, Mining and Telecommunications markets.



ADDITIONAL INFORMATION

Intel® Celeron® G4900T (2 Cores / 2 Threads, 2.9Ghz)

Processor Intel® Pentium® Gold G5400T (2 Cores / 4 Threads, up to

3.1Ghz)

Chipset Intel® Q370 Chipset (Coffee Lake)

Memory Sockets Supporting up to 64GB of RAM /

Memory

Optional Onboard RAID configurations (0, 1), requires multiple

Internal Storage drives

SATA III (6Gb/s and 3Gb/s) support

Internal Expansion Option (1) M.2 E-key, 2230

(1) M.2 M-key, 2280

Optional 2.5" Removable Drive Bay
Optical Drives
Optional Slim DVD-RW / CD-RW (SATA)

Optional DVD-RW / Blu-Ray Burner Serial ATA (SATA)

Video Intel® HD Graphics 610 (Intel® Celeron and Pentium Processors)

Includes DVI-I & DisplayPort video ports

(1) Integrated 10/100/1000 Base-T Intel® i219LM (3) Integrated 10/100/1000 Base-T Intel® i211AT

Networking Optional 801.11a/b/g/n/ac Dual Band (2.4GHz and 5GHz) +

Bluetooth via M.2 2230 Slot (Realtek RTL8822CE) PXE (Pre-Boot Execution Environment) Support

WoL (Wake On Lan) Support

Audio Integrated Realtek High Definition Audio CODEC ALC892

Windows 10 (64-bit) Windows Server 2019

Operating Systems Windows 10 IoT Enterprise

Ubuntu Linux

Please contact us directly for any special requirements

Chassis Description Low Profile Rugged Aluminum Chassis

10 - 48V DC Input

Power Input

Dinkle 5ESDAM-03 Mating Connector

Rear Locking 3-Pin power Jack ideal for mobile applications

No External AC Adapter included (optional AC supply available)



Dinkle 5ESDAM-03P Mating DC Connector

DVI to VGA Adapter

Included with System 4 Rubber Feet

Wall Mount Bracket

* NOTE: Subject to change without notice

(2) USB 3.1 Gen 2 Ports

2 PS/2 ports for Keyboard & Mouse

2x RS232 COM port

Rear Panel 1x Gigabit RJ45 Network connection

Audio Line-Out Jack

1x DVI-I video connector

1x DisplayPort video connector Locking 3-Pin DC Power Input Jack

(4) USB 3.1 Gen 2 Ports

3 x 10/100/1000 RJ45 Network connections

Microphone Input Jack

Front Panel Hard Drive indication LED

Power LED Light
Power-on button
Reset button

6.26" x 10.00" x 2.20" (159.0mm x 254.1mm x 55.9mm) [W x D

x H]

Operating Temperature: 0 - 40C (32 to 104 F)

Environmental Storage Temperature: -20 to 60C

Relative Humidity: 20% ~ 90% (Operating & Non-Operating)

Warranty 2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer Note: Specifications are subject to change without notice.

Dimensions