

LPC-810 - ULTRA SMALL PC 8GB, 480GB SSD, WIN 10 (QUICK SHIP SPECIAL)




\$1,505.00 USD

Rugged Fanless Small Form Factor PC

- No noise, Rugged Fanless Chassis
- Powerful Intel Celeron Mobile Processor
 - 8GB DDR3L memory
 - TPM 2.0
 - 480GB Solid State Drive (SSD)
 - 4x DIO (Digital input/output) ports
- Wide Range 9-48 VDC Input, ideal for mobile/field
- Built-in Gigabit LAN, USB 3.0/2.0, Audio, Serial, Video (DVI-I & Displayport)
- Windows 10 Professional 64-bit



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth LPC-810 is the smallest mini PC in Stealth's LPC-800 series line-up, weighing in at just 1.9 pounds (0.86kg), and can fit in the palm of your hand measuring just 5.9"(W) x 4.13"(D) x 1.9"(H) (150mm x 105mm x 49mm) in size.

It is RoHS, CE and FCC approved, and comes standard with Intel® Celeron® Processor J1900, Quad Core mobile processor and features four DIO (Digital input/output) ports. The 4 DIO ports with Isolation are ideal for reacting to motion sensors, or machinery status indicators, by ensuring signal integrity, especially in dusty, moist, and vibration prone industrial environments.

Fanless by design the LPC-810 makes it possible to employ the rugged mini PC for applications in challenging industrial environments. The aluminum chassis that houses the system of the LPC-810 model is heat-dispersing and impact resistant. The small fanless computer comes standard with a wide range 9-48 VDC input, ideal for mobile/field use, supported by built-in Gigabit LAN, USB 3.0/2.0, Audio, Serial, Video (DVI-I & Display) ports.

The LPC-800 series is fully customizable to your exact specifications, and designed for use in a multitude of industrial and commercial applications including: Audio/Video Recording, Embedded Control, Digital Signs, Interactive Kiosks, Thin-Clients, and Human/Machine Interface.

ADDITIONAL INFORMATION**Processor**

Supporting Intel® Celeron® Processor J1900, Quad Core, 2MB Cache, up to 2.42 GHz (standard)

BIOS

AMI 64Mbit SPI BIOS

Chipset

SoC integrated

Memory

8GB DDR3 Memory

Internal Storage

256GB SSD 3D Nand Drive

Internal Expansion Option

2 Internal full sized Mini-PCIe expansion slots

Video

Integrated Intel HD Graphics

Dual Display support with DisplayPort and DVI-I

2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported

LAN1 & LAN2: Intel I210-AT

Networking**Communications**

2x External SIM card sockets for wireless connectivity

Audio

Integrated Realtek High Definition Audio CODEC ALC888S

Operating Systems

Windows 10 (64-bit)

TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware security.

WatchDog Timer

1 ~ 255 sec/min

System Reset

Hardware Monitor

Processor temperature

Voltage

Chassis Description

Fanless Rugged Aluminum Chassis

Input is 9V - 48V DC

Power Mode: AT & ATX

Rear Locking 3-Pin power Jack ideal for mobile applications

Includes External AC Adapter, Input 100~240V AC @ 1.4A 50-60Hz

Power Input

Power Protection: OVP (Over Voltage Protection), OCP (Over Current Protection) & Reverse Protection

Included with System

North American Power Cord
Wall Mount Bracket
* NOTE: Subject to change without notice
100-240V AC Adapter, 4.75ft cable exit length

Rear Panel

2x RS232 COM port
4x DIO (Digital input/output) with Isolation
1x DVI-I video connector
1x DisplayPort video connector
9 – 48V DC Connector
2 x 10/100/1000 RJ45 Network connections
3 x USB 2.0 Ports
1 x USB 3.0 Port

Front Panel

Audio Line-Out Jack
Microphone Input Jack
AT / ATX Switch
Power-on button

Dimensions

5.9"(W) x 4.13"(D) x 1.9"(H) (150mm x 105mm x 49mm)

Operating Temperature: 0 – 40C (32 to 104 F)
Relative Humidity: 10% ~ 95%, non-condensing (Operating & Non-Operating)

Environmental

Shock: 50G, half sine, 11ms (with SSD)
Vibration: 5 Grms, 5 – 500 Hz, 0.5 hr/axis (with SSD)
Vibration: 1 Grms, 5 – 500 Hz, 0.5 hr/axis (with HDD)

Approvals

RoHS
CE
FCC

Weight

Unit Weight: 1.9 lbs / 0.86 KG

Warranty

2 Year limited Warranty, Standard
1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.