

17" LCD MONITOR / KEYBOARD 2U RACK DRAWER WITH 8 & 16 PORT KVM (FR-2002-17-KVM)



\$2,915.00 USD

Model: FR-2002-17-KVM

- KVM with 8, 12, or 16 Ports (DB-15, or DVI)
- 17" Slim 2U Rack LCD / Keyboard / Mouse
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 2U, 3.5" high
 - Built-in Keyboard & Touch Pad
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
 - Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, DC Power, Video Inputs



GALLERY IMAGES



PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 2U All-In-One LCD/Keyboard & Mouse with 8, 12, or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 3.5 inches or 2U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design

19" Rackmount steel chassis
2U , 3.5" or 88.9mm high
Latching front panel w/ 2-point lock

Screen Size

17.0" (Diagonal)

Type

TFT Active Matrix Liquid Crystal

Aspect Ratio

4:3

Native Resolution

1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)

Response Time

5ms Typical

Viewable Image Size

Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm

Video Signal

RGB Analog 0.7V Peak to Peak

Video Input Connectors

VGA / HD15 (Standard)
DVI-D (Optional)

Viewing Angle

80 (up), 80 (down), 80 (left), 80 (right)

Contrast Ratio

1000:1 (typical)

Luminance (Brightness)

250 cd/m2 typical at center (250 Nits)

Controls On-Screen Display

Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.

Input

Internal 100~240VAC, 50/60Hz Power Supply
Power Consumption: Max. 48 Watts, Standby 5 Watts

Built-in Keyboard / Mouse

104 Keys
3 Button Glide Point
PS/2 and USB Combo cables included

Environmental

Operating Relative Humidity (non condensing) 20-90%
Operating Temperature: 0~50C (32~122F)
Storage Temperature: -5~60C (-23~140F)
Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating)
Shock: 10G acceleration (11ms duration)
Vibration: 5~500Hz 1G RMS random vibration

Color

Black (standard)

Unit Weight	Unit Weight: 46.4 Lbs (21.1 kg)
Available Models	FR-2002-17-KVM8 – 17" LCD/Keyboard/Trackpad with 8-Port KVM (DB-15) FR-2002-17-KVM16 – 17" LCD/Keyboard/Trackpad with 16-Port KVM (DB-15)
Additional Options	Resistive/Capacitive Touchscreen 12/24/48VDC Power supply DVI-D, BNC, S-Video, RCA Inputs
Dimensions	19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)
Warranty	2 Year Parts & Labor