

19" LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH 8, 12 & 16 PORT KVM (FR-1002-19-KVM)



\$2,775.00 USD

Model: FR-1002-19-KVM

- KVM with 8, 12, or 16 Ports (DB-15 or DVI)
- 19" Slim 1U Rack LCD / Keyboard / Mouse
- Control multiple systems from one LCD
 - 8/16 Keyboard/Video/Mouse Inputs
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
- Field selectable for USB and PS/2
 - Built-in lockable Slide Rails
- Optional DC Power, Video Inputs
 - UL Approved



GALLERY IMAGES



PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 1U All-In-One LCD/Keyboard with 8 or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a touch pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

| | |
|-----------------------------------|--|
| Construction & Design | 19" Rackmount steel chassis 1U , 1.75" or 44.5mm high |
| Screen Size | 19.0" (Diagonal) |
| Type | TFT Active Matrix Liquid Crystal |
| Aspect Ratio | 4:3 |
| Native Resolution | 1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024) |
| Pixel Pitch | 0.294mm x 0.294mm |
| Response Time | 5ms Typical |
| Viewable Image Size | Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm |
| Video Signal | RGB Analog 0.7V Peak to Peak |
| Video Input Connectors | VGA / HD15 (Standard) DVI-D & HDMI (Optional) |
| Viewing Angle | 80 (up), 80 (down), 80 (left), 80 (right) |
| Contrast Ratio | 1000:1 (typical) |
| Luminance (Brightness) | 250 cd/m2 typical at center (250 Nits) |
| Controls On-Screen Display | Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc. |
| Input | Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 25 Watts, Standby 4 Watts 104 Keys |
| Built-in Keyboard / Mouse | 2 Button Touch Pad PS/2 and USB Combo cables included |
| Environmental | Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration |
| Color | Black (standard) |

| | |
|---------------------------|--|
| Unit Weight | Unit Weight: 27.9lbs (12.7 Kg) |
| Approvals | UL UL (Canada) |
| Available Models | FR-1002-19-KVM8 - 19" LCD/Keyboard/Touchpad with 8-Port KVM (DB-15) FR-1002-19-KVM16 - 19" LCD/Keyboard/Touchpad with 16-Port KVM (DB-15) KVM (Cat6) version with 8, 16 or 32 inputs available 12/24/48VDC Power supply |
| Additional Options | S-Video + Composite (BNC) + Audio input DVI-D or HDMI Input |
| Dimensions | 19.0"(W) x 1.75"(H) x 19.7 "(D) (482.6mm x 44.5mm x 500 mm) |
| Warranty | 2 Year Parts & Labor |