

## SR-1515 - HIGH PERFORMANCE 1U RACK MOUNT SERVER (DISCONTINUED)



### ***Model: SR-1515***

- 1U, High Performance Rack Mount PC Server
  - Slim Space Saving 1.75" (1U) High
- Powerful Single and Dual Intel Xeon Processors
  - Removable SAS Drives in RAID 1 or 0
    - Solid State Drive (SSD) options
- Server OS Support: 2012 R2, RHEL, SUEL & more
  - Built to your Exact Specifications
    - 2 Year Warranty

***Important - The model SR-1515 is now end-of-life and has been discontinued, if you have a requirement please contact us for assistance.***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model SR-1515 is a powerful space-saving Rack Mount PC Server that is only 1U (1.75") in height. Stealth's high performance 1U rack mount server features Single and Dual Intel Xeon Processors, up to 512GB DDR4 ECC memory, removable SAS drives in RAID configurations and one PCIe x16 expansion slot for an add-in card.

The SR-1515 is highly customizable and is compatible with Windows Server 2012 R2, Red Hat Linux Enterprise, Suse Linux Enterprise, Ubuntu, FreeBSD, CentOS, VMware and other operating systems. The SR-1515 can be built to your exact specifications using our online configurator below.

Stealth's 1U rack server is packed with features that would normally be found in much larger chassis, since rack space is at a premium this can provide significant cost savings in rack cabinet real estate. Our Rackmount Computer systems are ideal for telephony, industrial control, plant automation, ISPs, networking, machine vision, data acquisition and data center applications to name a few.

## **ADDITIONAL INFORMATION**

<b>Processor</b>	Supports Single or Dual Intel Xeon E5-2603 V3 (standard), or optional E5-2630 V3 processors
<b>Memory</b>	Dual-Channel ECC memory 16 DDR4 Memory Sockets Supporting up to 256GB per processor, 512GB Total RAM / Memory
<b>Internal Storage</b>	(2) 3.5" Removable Drive Bays, configured in a RAID 1 (standard), SAS Optional RAID 0 stripe Optional Support of Solid State Drives
<b>Drive Bays</b>	(1) 5.25" Bay, configured with a DVDRW/CDRW Optical (2) Removable 3.5" Drive Bays
<b>Expansion Slot(s)</b>	(1) PCIe x16 1U Riser Card
<b>Removable Storage</b>	DVDRW/CDRW Optical Drive offered standard (uses 1 x 5.25" Bay) Optional DVDRW/Blu-Ray Burner
<b>Video</b>	Integrated Graphics adapter, 16MB allocated and reported for Graphics controller Optional expansion graphics cards for higher video performance
<b>Ports</b>	(2) USB 2.0 / 1.1 Ports (rear-mount) (2) USB 3.0 / 2.0 Ports (rear-mounted) (1) VGA / HD-15 Video Dedicated Management NIC (DMN) Dual RJ45 10/100/1000 Gigabit Network Ports
<b>Power Supply</b>	100-240VAC, 50Hz – 60Hz, 500W power supply (standard) Meets 80PLUS Gold
<b>Operating Systems</b>	Microsoft: Windows Server 2012 R2, Windows Server 2008 R2 SP1, Windows 7 SP1 (32/64-Bit) Linux: Red Hat Enterprise Linux (RHEL) 6.5, Suse Linux Enterprise Server (SLES) 11 SP3, Ubuntu 14.04, FreeBSD 9.2, CentOS 6.5 VM Ware: ESXi 5.5 U2 Contact us for your specific operating system requirement to discuss compatibility

## Options

Solid State Drives (SSD) SATA  
Slide Rails  
3rd Party I/O Cards including RS232, RS485  
3rd Party Video or Acceleration Cards  
Video capture or input cards  
Contact us with any request for configuration

## Cooling Fans

Internal cooling bracket consisting of (5) cooling fans  
(2) Rear Exhaust Cooling Fans

## Environmental

Operating Temperature: 0~50C (32~122F)

## Dimensions

1.75"(H) x 19.00"(W) x 25.96"(D) (43.7mm x 482.6mm x 659.4mm)

## Weight

Approx. 40 lbs. depending on configuration

## Warranty

2 Year limited Warranty, Standard  
1 Year Extended Warranty available (see Configurator/Price List)

## Disclaimer

Note: Specifications are subject to change without notice.