

SR-2500P - SPACE SAVING 2U RACK COMPUTER / SERVER (12TH GEN)



\$2,110.00 USD

Model: SR-2500P

- 19" 2U Rack Mount Full Featured PC/Server
- Powerful 12th Generation Intel® Core™ Processors
- Massive Storage Options up to 28TB & up to 128GB of RAM
 - Single Redundant AC and DC Power Supply Options
 - PCle Expansion Slots
 - Custom Built to your Exacting Specifications
 - 2 Year Warranty





GALLERY IMAGES







PRODUCT DESCRIPTION

At only 3.5" high or 2U, the Stealth SR-2500P is a high performance space-saving 19" rack mount computer/server. The popular 2U Rack Computer / Server utilizes the latest Intel 12th Gen Core Processors & supports up to 128GB of memory, delivering the ultimate in computing power meeting your demanding business and application needs.

Standard configurations include a PCIe riser for additional add-in expansion cards. Up to (4) 5.25" drive bays are available to accommodate various storage (up to 28TB) and optical drives. High efficiency redundant AC and DC-power supplies are available for mission critical high-availability performance. Stealth has carefully selected, tested and qualified the highest quality of components to ensure the utmost in total system performance, reliability and long operational life cycles.

Stealth's Rackmount PC systems are ideal for telephony, industrial control, plant automation,
Datacenter/ISPs, IoT (Internet of Things), IIoT (Industrial Internet of Things), networking, machine vision,
and data acquisition applications to name a few.

Stealth Rack server products are designed to work on a continuous 24/7 basis yet are priced to meet your budget. Prior to shipping, each and every system is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.



ADDITIONAL INFORMATION

Supporting Intel®'s 12th Generation Core™ Processors (Alder

Lake)

Processor Intel® Core™ i3-12100 (4 Cores / 8 Threads, up to 4.30GHz)

Intel® Core $^{\text{TM}}$ i5-12500 (6 Cores / 12 Threads, up to 4.60GHz) Intel® Core $^{\text{TM}}$ i7-12700 (12 Cores / 20 Threads, up to 4.90GHz)

Intel® Core™ i9-12900 (16 Cores / 24 Threads, up to 5.10GHz)

Memory 4 DDR4 Memory Sockets supporting up to 128GB RAM / Memory

Optional Onboard RAID configuration (0, 1, 5, 10), requires

multiple drives

(4) 5.25" Open Bay (For use with 5.25" Optical Drives, internal

Hard Drives, removable drive bays, etc.)

(1) 3.5" Open Bay (For use with 3.5" Drives including 1.44MB

Floppy, Zip, etc.)

(1) 3.5" Internal optional cage for use with internal drive storage

(1) PCIe 3.0 x16 (Top Slot)

(1) PCIe 3.0 x4 (x8 physical, Middle Slot)

(1) PCIe 3.0 x1 (Bottom Restricted Slot)

Expansion Slot(s) 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110

storage devices support (PCIE 4.0 x 4 mode)

1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage

devices support (SATA & PCIE 4.0 x 4 mode)

Optional support for all Standard 5.25" Optical Disk Drives

Optional DVDRW/Blu-Ray Burner

Removable Storage
Optional Removable drive bay with Key locking (uses 5.25"

expansion bay)

Video Intel® UHD Graphics 770

Audio Realtek 7.1 Surround Sound High Definition Audio CODEC

TPM Module Optional TPM 2.0 (Trusted Platform Module), provides increased

hardware security.

Networking Onboard Realtek 2.5Gb Ethernet RJ-45

Optional support for Fiber, 10GB, Wireless and more

Drive Bays



(1) RJ45 2.5Gb Ethernet port

(1)USB 3.2 Gen 2 port (1 x USB Type-C®) (Rear mounted)

1x USB 3.2 Gen 1 port Type-A (Rear mounted)

2 x USB 2.0 ports Type-A (Rear Mounted)

Ports 2 x USB 3.2 Gen 1 (front-mount)

2 x USB 3.2 Gen 2 ports Type-A (Rear mounted)

(3) Audio Jacks (Input, Output and MIC)

(1) HDMI

(1) DisplayPort

90-264 VAC, 50Hz - 60Hz, 800W power supply (standard)

Power Supply Optional Redundant Power Supplies

Optional 12, 24, 48, 125 and more DC input available

Windows Server 2022

Windows 11 (64-bit) - Requires TPM 2.0

Operating Systems Windows 10 (64-bit)

Ubuntu Linux

Please contact us directly for any special requirements

Cooling Fans (3) Internal cooling fans, removable front filter

Environmental Operating Temperature: 0 - 45C (32 to 113 F)

Dimensions 3.5" H x 19.0" W x " 22.5"D (88.9mm x 482.6mm x 571.5mm)

Weight Approx. 50 lbs. depending on configuration

Warranty 2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer Note: Specifications are subject to change without notice.

Page: 4 May 5, 2024