

## SR-4000BL - INDUSTRIAL 4U RACK SERVER, 14 SLOT PASSIVE BACKPLANE



### **Model: SR-4000B**

- Feature Rich 4U 19" Rack PC/Server
- Open Expansion Slots, PCIe, PCI, ISA
- Passive Backplane & Single Board Computer Design
  - SBC Available in 14 Slot backplanes
  - Split Backplane Options Available
- Solid Steel Enclosure w/ Secure Front Door
- Multiple Drive Bays for Massive Storage
  - Various Power Supply Options
  - Front Cooling Fan & Filter
- Also available with ATX Mainboards
- Built to your Exact Specifications
  - 2 Year Warranty

***(Important Notice: The SR-4000BL model is now end of life and is replaced by the functional equivalent model SR-4000B.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model SR-4000BL: is a high performance Rack PC/Server system designed to work on a continuous 24/7 basis yet are priced to meet your budget. Stealth has carefully selected, tested and qualified the highest quality of components to ensure the utmost in total system performance, reliability and long operational life cycles.

The SR-4000BL: series Rack PC/Server supports numerous expansion slots for PCIe, PCI and ISA add-in cards. Systems are built and configured with passive backplane and single board computers also known as SBC that provide for open and available expansion slots. Stealth can offer various types of backplanes depending on your expansion slot needs.

Stealth's popular 4U Rack system with SBC and passive backplanes utilize the latest Intel processors designed to deliver the ultimate in computing power that you require to meet your business and application needs. Prior to shipping each and every system is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

## **ADDITIONAL INFORMATION**

**Processor**

Supporting Intel's Product Family including Intel Celeron, Pentium, Core 2 Duo, Core 2 Quad and Xeon processors

**Memory**

Supporting Single or Dual-Channel memory architecture  
Options starting at 512MB

**Internal Storage**

Supports all SATA (Serial-ATA) I & II Hard Drives  
Optional support for SAS (Serial Attached SCSI), SCSI or Solid State Hard Drives (SSD)

Optional RAID configurations (0, 1, 5, 10 and more)

Shock mounted Drive Cage

**Drive Bays**

(6) 5.25" Open Bay (For use with 5.25" Optical Drives, internal Hard Drives, etc.)

(1) 3.5" Open Bay (For use with 3.5" Drives including 1.44MB Floppy, Zip, etc.)

Customized solutions for hot swap / removable drive assemblies

Featuring a 14-Slot backplane layout

Options supported for PICMG 1.0 and 1.3

**Expansion Slot(s)**

Combinations of PCI, ISA and PCIe (PCI Express) available

Up to 10 Full length expansion slots (depending on configuration)

Includes Expansion card hold down bracket

DVDRW/CDRW Optical Drive offered standard (uses 1 x 5.25" Bay)

**Removable Storage**

Optional support for all Standard 5.25" Optical Disk Drives

Optional DVDRW/Blu-Ray Burner

Optional Removable drive bay with Key locking (uses 5.25" expansion bay)

**Video**

Standard Video included onboard with Single Board Computer (SBC)

Optional 3rd party graphics cards available in PCI or PCIe (PCI Express)

**Ports**

Generally supplied with 1 Serial (RS-232) port, LPT Port and 2 USB ports

(Depending on configuration, please contact Stealth to determine your needs)

2 USB 2.0 ports (front-mount) standard

## Power Supply

100-240 VAC, 50Hz – 60Hz, 650W power supply (standard)  
Meets 80PLUS Platinum

## Operating Systems

Windows 7 (32 and 64-bit)  
Windows 8.1 (32 and 64-Bit)  
Windows Server 2003  
Windows Server 2008  
Windows Server 2012 R2  
Ubuntu Linux  
Please contact us directly for any special requirements

## Options

Solid State Drives (SSD) SATA  
Removable drive bays  
SCSI interface and hard drives  
SAS (Serial attached SCSI) Drives and controllers  
RAID  
Slide Rails  
DC input power options  
3rd Party I/O Cards including RS232, RS485  
3rd Party Video or Acceleration Cards  
Video capture or input cards  
Contact us with any request for configuration

## Cooling Fans

Dual front intake Cooling Fans  
Removable Front Intake Filter  
Full-length latching/locking door

## Environmental

Operating Temperature: 0~50C (32~122F)

## Dimensions

7.0" H x 19.0" W x 26.5" D (178mm x 482mm x 671mm)

## Weight

Approx. 40 lbs. depending on configuration

## Warranty

2 Year limited Warranty, Standard  
1 Year Extended Warranty available (see Configurator/Price List)

## Disclaimer

Note: Specifications are subject to change without notice.