

## SR-28302 - FANLESS 2U RACKMOUNT PC - DUAL SYSTEM (DISCONTINUED)



### ***Fanless, Dual System Rack PC***

- Two Systems in the Same Space as One
  - Fanless, Noise Free Computing
  - Space Saving 2U, 3.5" Rack Server/PC
- Powerful Intel 5th Gen Core i5 or i7 Mobile Processor
  - 4x DIO (Digital input/output) ports
  - Removable Front Drive Bay
- Wide Range 9-48 VDC Input, ideal for mobile/field
  - Solid State Drives (SSD) Standard
  - Windows 7, 8.1, 10 and Linux
  - Single System Option also available
- Wide Temperature Version also available

***(Important Notice: The SR-28302 model is now end of life, please contact us if you have a requirement.)***





## GALLERY IMAGES



## PRODUCT DESCRIPTION

Fanless by design, Stealth's fanless high performance Rack PC is available in single or dual system designs all built-in to a slim 3.5" high (2U) rack mountable steel chassis with locking front door.

Stealth's SR-28302 is a noise free dual system rackmount Server/PC, allowing for two computers in the same space as one. Each system is equipped with a powerful Intel 5th Gen Core i7 Mobile Processor and is equipped with 128GB solid state drive(SSD), upgradeable to 1TB, as well as 4GB of RAM - upgradeable to 8GB.

Stealth's fanless system operates without noisy cooling fans that can draw in dirt and dust causing potentially catastrophic failures. The space saving design features a rugged extruded aluminum chassis that provides superior heat dissipation. See our FAQ - Why Choose Fanless?

The SR-28302 has an abundance of ports per system; 4x DIO (Digital input/output) with Isolation, offering the advantage of providing electrical isolation of digital signals. Also included are USB 3.0/2.0 ports, RS232 COM ports, Gigabit networking and audio/video ports. Along with the high number of ports, the SR-28302 houses a Removable Front Drive Bay on each system, providing easy drive swapping and making customization a breeze.

The SR-28302 fanless rack mount computer is RoHS, CE & FCC certified, and designed for use in a multitude of applications including; Audio/Video recording, Embedded Control, Digital Signs, Interactive Kiosks, Thin-Clients, and Human/Machine Interface.

**ADDITIONAL INFORMATION****Processor**

Supporting Intel® 5th Gen Core™ Processor i5-5350U, Dual Core, 3MB Cache, up to 2.9 GHz (standard)  
Optional Intel® 5th Gen Core™ Processor i7-5650U, Dual Core, 4MB Cache, up to 2.2 GHz

**BIOS**

AMI 128Mbit SPI BIOS

**Chipset**

SoC integrated

**Memory**

4GB DDR3L SO-Dimm RAM (standard), option of 8GB available

**Internal Storage**

Includes 1 Internal Drive Bay  
Includes 1 Removable Drive Bay  
256GB 3D NAND SSD (Solid State Drive) standard (SATA)  
Options of up to 1TB SSD internal storage.  
Optional Onboard RAID configurations (0, 1), requires multiple drives

**Internal Expansion Option**

2 Internal full sized Mini-PCIe expansion slots

**Video**

Integrated Intel HD Graphics 6000  
Includes DVI-I & DisplayPort video ports  
Triple Display support with DisplayPort and DVI-I  
Max Resolution, DisplayPort Mode: 3840x2160 @ 60Hz, DVI Mode: 1920 x 1200 @ 60Hz

**Networking**

2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported  
LAN1: Intel I210-AT, LAN2: Intel I218-LM  
Optional 4 x 10/100/1000 RJ45 POE Network connections on Front Panel  
Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe

**Communications**

2x External SIM card sockets for wireless connectivity

**Audio**

Integrated Realtek High Definition Audio CODEC ALC888S

## **Operating Systems**

Windows Server 2019  
Windows 7 (32 and 64-bit)  
Windows 10 (64-bit)  
Windows 8.1 (32 and 64-Bit)  
Windows Server 2016

Ubuntu Linux

Please contact us directly for any special requirements

## **TPM Module**

Trusted Platform Module (TPM) 1.2, provides increased hardware security.

## **WatchDog Timer**

1 ~ 255 sec/min  
System Reset

## **Hardware Monitor**

Processor temperature  
Voltage

## **Chassis Description**

2U, 3.5" High, 19" EIA rackmount  
Solid Steel Chassis, Black Color  
Locking / Latching Secure Front door  
Fanless Design

## **Power Input**

Input is 9V - 48V DC  
Power Mode: AT & ATX  
Rear Locking 3-Pin power Jack ideal for mobile applications  
Includes External AC Adapter, Input 100~240V AC @ 1.4A 50-60Hz  
Power Protection: OVP (Over Voltage Protection), OCP (Over Current Protection) & Reverse Protection

## **Included with System**

North American Power Cord  
\* NOTE: Subject to change without notice  
100-240V AC Adapter, 4.75ft cable exit length

## **Options**

Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth, Intel® AC7260 via internal Mini-PCIe  
External USB DVD+-RW/CD-RW Drive

## **Rear Panel**

2 x RS232 COM port  
2x Gigabit RJ45 Network connection  
4x DIO (Digital input/output) with Isolation  
Audio Line-Out Jack  
Microphone Input Jack  
2 x USB 3.0 Ports  
2 x USB 2.0 Ports  
1x DVI-I video connector  
1x DisplayPort video connector  
9 - 48V DC Connector

## Front Panel

4 x 10/100/1000 RJ45 POE Network connections (optional)  
4 x USB 2.0 Ports  
2 x RS232 COM port  
AT / ATX Switch  
Power-on button

## Dimensions

19.0"(W) x 13.94"(D) x 3.468"(H) (482.6 x 354 x 88 mm)

## Environmental

Operating Temperature: 0 - 40C (32 to 104 F)  
Relative Humidity: 10% ~ 95%, non-condensing (Operating & Non-Operating)  
Shock: 50G, half sine, 11ms (with SSD)  
Vibration: 5 Grms, 5 - 500 Hz, 0.5 hr/axis (with SSD)  
Vibration: 1 Grms, 5 - 500 Hz, 0.5 hr/axis (with HDD)

## Approvals

RoHS  
CE  
FCC

## Weight

Unit Weight: 4.58 lbs / 2.08 KG

## Warranty

2 Year limited Warranty, Standard  
1 Year Extended Warranty available (see Configurator/Price List)

## Disclaimer

Note: Specifications are subject to change without notice.