

SR-2955 - FANLESS 2U RACKMOUNT SERVER/PC WITH NVIDIA VIDEO (WIDE RANGE TEMPERATURE)



\$4,395.00 USD

Fanless 2U Rackmount PC with Nvidia Video

- Fanless, Noise Free Computing
- Space Saving 2U, 3.5" Rack Server/PC
- Powerful Intel® 6th and 7th Generation Core™ i5, i7 & Xeon processors
 - ECC Memory Support
- Dedicated NVIDIA® GeForce® Quadro T1000 graphics card
 - Supports up to 8K resolution, 7 Display support
 - 32 DIO (16 In/16 Out Digital input/output) ports
 - Dual Removable Front Drives
- Wide Operating Temperature (-25°C – 60°C / -13°F – 140°F)
 - PCIe x4 expansion slot
- Wide Range 10-36 VDC Input, ideal for mobile/field
 - Windows 10, 10 IoT, Server 2022, and Linux
 - RoHS, CE & FCC, EN50121-3-2, EN50155 certified
 - Small Form Factor model version also available



GALLERY IMAGES



PRODUCT DESCRIPTION

The new Stealth SR-2955 Wide Temperature Rack Mount PC is our latest in innovative Fanless 2U Rackmount Computers/Servers. It features a dedicated NVIDIA® graphics card, along with Intel® 6th and 7th Generation Core™ i5, i7 & Xeon processors and supports operation in temperatures ranging from -25°C – 60°C. The robust capabilities packed into a 2U high rack mount chassis make it ideal for installation in standard 19" EIA rack cabinets.

The SR-2955 Rack Mount PC comes equipped with a dedicated NVIDIA® GeForce Quadro T1000 graphics card supporting up to 8K Resolution across 4 DisplayPort video ports. In combination with the Intel onboard video (DVI-D, VGA and 2 DisplayPort video ports), up to 7 displays can be connected simultaneously.

Fanless by design, the system operates without noisy cooling fans that can draw in dirt and dust causing potentially catastrophic failures. The space saving design features a rugged extruded aluminum chassis that provides superior heat dissipation within a 2U high 19" rack mount chassis.

The SR-2955 can be configured with 256GB to 4TB of total SSD storage (using dual drives), as well as 8GB to 64GB of RAM. ECC memory is available depending on the CPU selected. Also included are dual Removable Front Drive Bays that provide easy drive swapping and onboard Raid supporting 0/1 set-up options. The powerful small form factor PC includes an abundance of I/O ports such as USB 3.0, RS232 Serial, Gigabit networking, 32 DIO (Digital input/output), external SIM card sockets for wireless connectivity and audio/video ports.

Engineered to be extremely mobile friendly, the SR-2955 includes a Wide Range 10-36 VDC power input with a rear locking 3-Pin Ignition Switch. A TPM 2.0 (Trusted Platform Module) is incorporated to provide increased hardware security.

The SR-2955 is RoHS, CE, FCC, EN50121-3-2 & EN50155 certified and designed for use in a multitude of applications including: Audio/Video Recording, Embedded Control, Digital Signs, Interactive Kiosks, IoT, Industrial Internet of Things (IIoT), Transportation, and Human/Machine Interface.

ADDITIONAL INFORMATION

Processor	Supporting Intel® Core™ 6th and 7th Generation, and Xeon® Processors Intel® Celeron® G3900TE (2 Cores / 2 Threads, 2.30Ghz) Intel® Core™ i5-6500TE (4 Cores / 4 Threads, up to 3.30Ghz) Intel® Core™ i7-6700TE (4 Cores / 8 Threads, up to 3.40Ghz) Intel® Core™ i7-7700T (4 Cores / 8 Threads, up to 3.80Ghz) Intel® Xeon® E3-1268L v5 (4 Cores / 8 Threads, up to 3.40Ghz)
BIOS	AMI
Chipset	Intel® C236
Memory	2x DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory Optional ECC Memory Support (available for Celeron and Xeon CPUs only)
Internal Storage	256GB TLC SSD (Solid State Drive) Wide Temp standard (SATA) Options of up to 2TB SSD internal storage. Optional Onboard RAID configurations (0, 1), requires multiple drives
Internal Expansion Option	(3) Full-Sized MiniPCIe Slots PCIe x4 expansion slot (Up to 7" length) NVIDIA® GeForce® 1050Ti or Quadro T1000 providing 4x DisplayPorts Supports 8K UHD and 4K UHD Resolution as well as 1080p HD Video
Video	Up to 7 independent displays total (3 video ports using onboard Intel chipset) Includes 1 VGA, 1 DVI and 6 DisplayPort video ports – 1 VGA : Up to 1920 x 1200 @ 60Hz – 1 DVI : Up to 1920 x 1200 @ 60Hz – 2 DisplayPort : Up to 4096 x 2304 @ 60Hz – 4 DisplayPort : Up to 7680 x 3840 @ 60Hz

Networking

LAN1: Intel® I219LM, LAN2: Intel® I210
2 onboard Gigabit Ethernet controllers, RJ-45 interface, PXE and WOL Supported
Optional 802.11 b/g/n/ac Dual Band (2.4Ghz / 5Ghz) Wireless Networking and Bluetooth 4.0, Realtek® RTL8821AE via internal Mini-PCIe

Communications

3x External SIM Card sockets for wireless connectivity

Audio

Integrated Realtek High Definition Audio CODEC ALC892, 5.1 Channel HD Audio

Operating Systems

Windows Server 2022
Windows 10 (64-bit)
Windows 10 IoT Enterprise
Ubuntu Linux

TPM Module

TPM 2.0 (Trusted Platform Module), provides increased hardware security.

Chassis Description

2U, 3.5" High, 19" EIA rackmount
Fanless Rugged Aluminum Chassis

Power Input

Input is 10V – 36V DC
Rear Locking 3-Pin Ignition Switch (12V or 24V)
Rear Locking 3-Pin power Jack ideal for mobile applications
AC Adapter

Included with System

North American Power Cord
* NOTE: Subject to change without notice

Rear Panel

10 – 36V DC Connector
1x Expansion Slot
32 DIO (16 In/16 Out Digital input/output)
4x DisplayPort Video connectors
4x RS232 COM ports
Rear Locking 3-Pin Ignition Switch (12V or 24V)
2 x USB 3.0 Ports

Front Panel

(2) Removable 2.5" Drive Bays
1x Analog VGA / HD-15
1x DVI-D video connector
2x DisplayPort Video connectors
2x Gigabit RJ45 Network connections
3x SIM Card Communication Slots
4x USB 3.0 Ports
Audio Line-Out Jack
Microphone Input Jack
Power-on button
Reset button

Dimensions

19.0"(W) x 8.5"(D) x 3.5"(H) (483mm x 215mm x 89mm)

Operating Temperature: -25°C – 60°C (-13°F – 140°F)

Shock: IEC 60068-2-27, SSD: 50G @ wallmount, Half-sine, 11ms

Storage Temperature: -10C – 60C (14F – 140F)

Environmental

Vibration: IEC 60068-2-64, SSD: 5Grms, 5Hz to 500Hz, 3 Axis

Humidity: 5% ~ 95%, non-condensing (Operating & Non-Operating)

EN50121-3-2

EN50155

Approvals

RoHS

CE

FCC

Weight

22lbs (10kg)

Warranty

2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.