

SR-4550A - SHORT DEPTH 4U RACK COMPUTER (AMD)



Model: SR-4550A

- Only 11.88" Deep, Ideal for shallow racks
- 19" Rack Mount Full Featured PC/Server
 - Powerful AMD Ryzen Processors
 - 4U, Solid Steel Enclosure Front Door
- Multiple Drive Bays for Massive Storage
 - Various Power Supply Options
 - Optional Stealth HMI Software
 - Built to your Exact Specifications
 - 2 Year Warranty





GALLERY IMAGES







PRODUCT DESCRIPTION

Less than 12" deep, Stealth's model: SR-4550A short depth 4U Rack computer / server, is a space saving high performance machine – enclosed in a small footprint all-steel chassis, now available with powerful AMD Ryzen processors.



The available SR-4550A configurations include AMD's Ryzen 3, 5, and 7 high performance processors. What makes the Ryzen processors so special is that the Ryzen series has changed the game in its multithreaded performance benchmarks.

Each AMD Ryzen chip is equipped with with SenseMI technology to boost performance and increase computing speeds. If your tasks include, streaming, encryption, productivity and content creation - the Ryzen chipset is your go to for high performance.

With each machine we build, Stealth engineers carefully select, test, and qualify each model to the highest standards of excellence in components, to ensure the utmost in total system performance, reliability and long operational life cycles.

The SR-4550A configurations include expansion slots for add-in PCIe cards, as well as plenty of storage space with up to 4 drives with SSD (Solid State Drive) options. Multiple options for DC input power supplies are also available.

Stealth Rack server products are designed to work on a continuous 24/7 basis yet are priced to meet your budget. Prior to shipping, each and every system is put through Stealth's rigorous QA burn-in



procedure that is documented and controlled through our ISO 9001 quality system.



ADDITIONAL INFORMATION

Processor	AMD Ryzen 3 2200G, Ryzen 5 2400G, and Ryzen 1700 Customized options for AMD Opteron processors Optional support for AMD 7th Generation A-Series / Athlon Processors
Memory	Dual-Channel memory architecture 4 DDR4 Memory Sockets Supporting up to 64GB of RAM / Memory
Internal Storage	2 x 2.5" Internal Drive bays Optional 4 x 2.5" with Removable Drive Bay Optional Onboard RAID configurations (0, 1, 10), requires multiple drives
Drive Bays	2 x 5.25" External Drive Bays Customized solutions for hot swap / removable drive assemblies
Expansion Slot(s)	1 x PCle x16 3.0 Slot – Populated with video card 2 x PCle x1 2.0 Slots
Removable Storage	DVDRW/CDRW Optical Drive offered standard (uses 1 x 5.25" Bay) Optional support for all Standard 5.25" Optical Disk Drives Optional DVDRW/Blu-Ray Burner Up to 4 x optional Removable drive bays with Key lock (uses 5.25" expansion bay) 1024MB, DVI-D, HDMI and VGA
Video	Max Resolution 4096 x 2160 (Digital) Multi-Display, Triple Screens
Audio	Onboard 8-Channel High Definition Audio CODEC
Networking	Optional support for Wireless and additional Networking options Onboard 10/100/1000Base-T Gigabit LAN, RJ-45
TPM Module	Optional TPM 2.0 (Trusted Platform Module), provides increased hardware security.

STEALTH

Ports	 (2) USB 3.1 Gen 2 Ports (rear-mounted) (4) USB 3.1 Gen 1 Ports (rear-mounted) (2) USB 2.0 / 1.1 ports (front-mount) (1) RJ45 10/100/1000 BASE-T Gigabit LAN Port (3) Audio Jacks (Input, Output and MIC) (2) PS/2 ports for Keyboard & Mouse (1) VGA / HD-15 Video (1) DVI-D (Digital Only) (1) HDMI (1) Optional onboard DB9 Serial / RS232 Standard with 100-240 VAC, 50Hz - 60Hz, 650W power supply
Power Supply	(standard) Meets 80PLUS Gold Optional 24 (18-36), 48 (37-71), 120 (80-150) and 220 (190-260)
Operating Systems Options	DC inputs available Windows 10 (64-bit) Windows 7 (64-bit) Please contact us directly for any special requirements Solid State Drives (SSD) SATA Removable drive bays SAS (Serial attached SCSI) Drives and controllers RAID Slide Rails DC input power options
Cooling Fans	3rd Party I/O Cards including RS232, RS485 3rd Party Video or Acceleration Cards Video capture or input cards Contact us with any request for configuration Dual front intake Cooling Fans Removable Front Intake Filter
Environmental	Operating Temperature: 0~50C (32~122F)
Dimensions	7.0" H x 19.0" W x 11.88" D (178mm x 482mm x 301.8mm)
Weight	25-30lbs, 13-16 Kg (Depending on configuration)
Warranty	2 Year limited Warranty, Standard 1 Year Extended Warranty available (see Configurator/Price List)
Disclaimer	Note: Specifications are subject to change without notice.