

102-DP-FSR-BL - RUGGED ILLUMINATED KEYBOARD



\$500.00 USD

Illuminated/Backlit industrial keyboard with Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
 - Backlighting / Illumination
 - ABS-Polycarbonate Sealed Plastic Case
 - 102 Keys, 12 Function Keys
 - Built-in Finger Tip Mouse (Pointing Device)
 - Greater than 10 Million cycles expected life
 - PS/2 or USB connectors
- Optional "Mobile" enclosure w/ bottom mounting studs



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth Computer model 102-DP-FSR-BL is an excellent solution for space saving needs. An ultra-thin and compact unit, it measures only 1.05 inches in height, while featuring an integrated 3 button Finger Tip Mouse pointing device, eliminating the need for an external mouse. For working in low-light situations, the 102-DP-FSR-BL keyboard even comes with backlit keys.

The environmentally sealed (NEMA & IP rated) enclosure is intended for indoor or outdoor use primarily to provide a degree of protection against corrosion, windblown dust and rain, splashing water, and hose-directed water; and to be undamaged by the formation of ice on the enclosure.

Stealth's industrial keyboards and pointing devices are also available in stainless steel, desktop, panel mount, rack mount, open-frame, kiosk/public access and with illuminated / backlit features.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 210 mA @ 5V (from Keyboard Port)

Power

PS/2 Mouse: 35mA @ 5V (from Mouse Port)

USB: 245 mA @ 5V (from USB port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% Humidity Resistant

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Backlighting / Illumination

Red LEDs (On/Off)

Dimensions

Mobile Version: 14.74" (w) x 5.69" (h) x 1.64" (d) (374.4mm x 144.5mm x 41.7mm)

Standard Version: 14.6" (w) x 5.55" (h) x 1.05" (d) (370.84mm x 140.97mm x 26.67mm)

Cable

Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most Linux/Unix Systems

Additional Options

Custom cable lengths, special connectors, custom enclosures etc

Other Languages Available - Contact us for more details, Minimum quantities may apply.

Warranty

1 Year limited Warranty Standard

Model Numbers

102-DP-FSR-BL-M-PS/2-RED - Mobile Version, PS/2 Interface

102-DP-FSR-BL-M-USB-RED - Mobile Version, USB Interface

102-DP-FSR-BL-PS/2-RED - Standard Version, PS/2 Interface

102-DP-FSR-BL-USB-RED - Standard Version, USB Interface

Disclaimer

Note: Specifications are subject to change without notice.