

## 75-DT-BL - RUGGED ILLUMINATED/BACKLIT KEYBOARD



**\$349.00 USD**

### *Small Desktop Backlit Keyboard*

- Sealed to NEMA 4, 4X / IP65 specifications
  - Backlit / Illumination
  - Small Foot Print Design
  - 75 Keys including 12 Function Keys
- Greater than 10 Million cycles expected life
  - PS/2 or USB connectors



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model 75-DT-BL is a NEMA 4, 4X / IP65, waterproof, dust-proof, and backlit keyboard that is ideal for industrial, kiosk and mobile computing applications. It is a highly versatile keyboard that offers a high value solution for a low price and offers both USB and PS/2 interfaces.

The 75-DT-BL features red LEDs providing bright keyboard illumination ideal for dark or low light areas.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

**ADDITIONAL INFORMATION**

<b>Industrial Approvals</b>	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
<b>Key Switch</b>	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 135g (+/- 30g), 4.76 oz. +/- 1.06 oz. Feedback: Tactile with mechanical snap
<b>Power</b>	PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port) USB Keyboard: 200mA @ 5V from USB port
<b>Temperature Range</b>	Operating: -40C to +70C (-40F to +158F) Storage: -40C to +90C (-40F to +194F)
<b>Humidity</b>	100% Humidity Resistant
<b>Shock</b>	3x11 ms pulses of 50g on each of 3 axes
<b>Vibration</b>	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
<b>Backlighting / Illumination</b>	Red LEDs (On/Off)
<b>Dimensions</b>	8.25" (w) x 4.34" (h) x 1.08" (d) [209.6mm x 110.2mm x 27.4mm]
<b>Cable</b>	Length: 10' (3.04 meters)
<b>Compatibility</b>	Compatible with all Windows Operating Systems
<b>Warranty</b>	1 Year Parts & Labor
<b>Model Numbers</b>	75-DT-BL-PS/2 - PS/2 Interface 75-DT-BL-USB - USB Interface
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.