

75-SL - RUGGED ILLUMINATED/BACKLIT KEYBOARD (DISCONTINUED)



Small Desktop Backlit Keyboard

- Sealed to NEMA 4, 4X / IP65 specifications
 - Backlighting / Illumination
 - Small Foot Print Design
 - 75 Keys including 12 Function Keys
- Greater than 10 Million cycles expected life
 - PS/2 or USB connectors

(Important Notice: The 75-SL model is now end of life and is replaced by the functional equivalent model 75-DT-BL.)



PRODUCT DESCRIPTION

The Stealth Computer model 75-SL is a NEMA 4X, waterproof, dust-proof, and backlit keyboard that is ideal for industrial, kiosk and mobile computing applications. It is a highly versatile keyboard that offers a high value solution for a low price. The 75-SL features red LEDs providing bright keyboard illumination.

ADDITIONAL INFORMATION

Industrial Approvals	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
Key Switch	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.060" (1.5mm) Actuation Force: 5oz (130g) Feedback: Tactile with mechanical snap
Power	PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port) USB Keyboard: 200mA @ 5V from USB port
Temperature Range	Operating: -40C to +70C (-40F to +158F) Storage: -40C to +90C (-40F to +194F)
Humidity	100% (when properly installed)
Shock	3×11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Backlighting / Illumination	Red LEDs (On/Off)
Dimensions	(W-H-D) 8.25" x 4.38" x 1.0" (209.6mm x 111.3mm x 25.4mm)
Cable	Length: 10 feet (3.94 meters), Design: PS2 or USB
Compatibility	Compatible with all Windows Operating Systems Custom cable lengths, special connectors, custom enclosures etc
Additional Options	Other Languages Available – Contact us for more details, Minimum quantities may apply.
Warranty	1 Year limited Warranty Standard
Model Numbers	75-SL-PS/2 (PS/2 Interface) 75-SL-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.