

911-86-SL-TP - SMALL FOOTPRINT KEYBOARD WITH BUILT-IN TOUCHPAD MOUSE (DISCONTINUED)



Sealed Illuminated Keyboard/Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
 - Backlighting / Illumination
 - ABS-Polycarbonate Sealed Plastic Case
 - Small Foot Print Design
- 86 Keys, 12 Function Keys, Emergency Key, FN Key
 - Built-in Touchpad Mouse
- Greater than 10 Million cycles expected life
 - PS/2 or USB connectors

***(Important Notice: The 911-86-SL-TP model is now
end of life and is replaced by the functional
equivalent model 880-DP-TP-BL.)***



PRODUCT DESCRIPTION

The Stealth Computer model 911-86-SL-TP offers both a rugged keyboard and rugged touchpad mouse in one compact package. It boasts a completely sealed and ruggedized construction that allows it to meet NEMA 4X / IP65 specifications. The 911-86-SL-TP's backlighting is available with Red LEDs and provides bright keyboard illumination. Additionally, the 911-86-SL-TP features a specially designed Emergency key that when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. The 911-86-SL-TP is available with PS/2 or USB connectors.

ADDITIONAL INFORMATION**Industrial Approvals**

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port)

Power

PS/2 Mouse: 10mA @ 5V (from mouse port)

USB: 210 mA @ 5V (from USB port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% (when properly installed)

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Backlighting / Illumination

Red LEDs (On/Off)

Dimensions

(W-H-D) 12.0" x 7.74" x 1.27" (304.8mm x 196.6mm x 32.3mm)

Cable

Design: 4 Feet (1.2 meters) Single 4' "Y-Split" Coiled Cable with PS/2 Connectors, or Single USB Cable

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most

Linux/Unix Systems

Custom cable lengths, special connectors, custom enclosures etc

Additional Options

Other Languages Available – Contact us for more details,

Minimum quantities may apply.

Warranty

1 Year limited Warranty Standard

Model Numbers

911-86-SL-TP-PS/2 (PS/2 Interface)

911-86-SL-TP-USB (USB Interface)

Disclaimer

Note: Specifications are subject to change without notice.