

2000-PM-FSR-NI - NON-INCENDIVE PANELMOUNT KEYBOARD



\$795.00 USD

Sealed Non-Incendive Safe Keyboard, w/ Built-in Mouse

- Non-Incendive for use in hazardous environments
- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - Panelmount Stainless Steel Case
 - Includes Bulkhead Connectors
- 114 Keys, 24 Function Keys & 10-Key Numeric Pad
 - Built-in 3 button Pointing Device
 - Greater than 10 Million cycles expected life
- Includes separate PS/2 or USB cables with Bulkhead connectors



PRODUCT DESCRIPTION

The Stealth model 2000-PM-FSR-NI is a Non-Incendive Panelmount Keyboard that is environmentally sealed to NEMA 4, 4X / IP65 specifications (when properly installed) and designed to operate in hazardous locations including wet, dirty or harsh environments.

This rugged keyboard with stainless steel bezel includes 114 Keys in total, 24 Function Keys, 10 Key numeric keypad and a built-in 3 button pointing device mouse. The 2000-PM-FSR-NI has a Factory Mutual approval for Class I, Division II, Groups A, B, C, and D. All units include isolation barrier.

The 2000-PM-FSR-NI ships with rear gaskets to ensure a watertight seal into panels, kiosks or consoles. The 2000-PM-FSR-NI is available with a USB or PS/2 interface.

ADDITIONAL INFORMATION

Weight	8 lbs
Industrial Approvals	FM Approved for Class I Division II, Groups: A, B, C, D NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B * Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65) Material: Industrial Silicone Rubber Life: Greater than 10 million cycles
Key Switch	Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
Power	Please Reference Drawing for Power Requirements. Installation shall be in accordance with NEC, Article 504, ANSI, NFPA 70.
Temperature Range	Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
Humidity	100% (when properly installed)
Shock	3x11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Dimensions	(W-D-H) 21.80" x 9.20" x 0.28" (553.7mm x 233.7mm x 7.1mm)
Cable	Length: 5 feet from keyboard to Bulkhead Connector Design: separate cables (providing separate keyboard and mouse connections)
Compatibility	Compatible with all Windows Operating Systems
Weight	Contact Us
Warranty	1 Year limited Warranty Standard
Model Numbers	2000-PM-FSR-NI-PS/2 (PS/2 Interface) 2000-PM-FSR-NI-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.