

## 5000-DT-FSR-NI - NON-INCENDIVE DESKTOP KEYBOARD



### ***Sealed Non-Incendive Safe Keyboard, w/ Built-in Mouse***

- Non-Incendive for use in hazardous environments
- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Rugged Stainless Steel Case
  - Includes Bulkhead Connectors
- 112 Keys, 20 Function Keys, WIN KEY
  - Built-in 3 button Pointing Device
- Greater than 10 Million cycles expected life
- Includes separate PS/2 or USB cables with Bulkhead connectors

**Please contact us if you have a requirement for this model.**



## **PRODUCT DESCRIPTION**

The Stealth model 5000-DT-FSR-NI is a Non-Incendive Desktop Keyboard that is environmentally sealed to NEMA 4, 4X / IP65 specifications and designed to operate in hazardous locations including wet, dirty or harsh environments.

This rugged keyboard with stainless steel bezel includes 112 Keys in total, 20 Function Keys, 22 Key numeric keypad and a built-in 3 button pointing device mouse. The 5000-DT-FSR-NI has a Factory Mutual approval for Class I, Division II, Groups A, B, C, and D. All units include isolation barrier.

The 5000-DT-FSR-NI is available with a USB or PS/2 interface.

## ADDITIONAL INFORMATION

### Industrial Approvals

FM Approved for Class I  
Division II, Groups: A, B, C, D  
NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

### Key Switch

Material: Industrial Silicone Rubber  
Life: Greater than 10 million cycles  
Travel: 0.060" (1.5mm)  
Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)  
Feedback: Tactile with mechanical snap

### Temperature Range

Operating: -20C to +60C (-4F to +140F)  
Storage: -40C to +70C (-40F to +158F)

### Humidity

100%

### Shock

3×11 ms pulses of 50g on each of 3 axes

### Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,  
Duration of Test per Axis: 3 hours

### Dimensions

(W-H-D) 16.25" x 7.9" x 1.9" (412.8mm x 200.7mm x 48.3mm)

### Cable

Length: 5 feet from keyboard to Bulkhead Connector  
Design: separate cables  
(providing separate keyboard and mouse connections)

### Compatibility

Compatible with all Windows Operating Systems

### Weight

Unit: 5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)

### Warranty

1 Year limited Warranty Standard

### Model Numbers

5000-DT-FSR-NI-PS/2 (PS/2 Interface)

### Disclaimer

Note: Specifications are subject to change without notice.