

## KYBX-400-PM-BL-TB-USB - VANDAL RESISTANT PANELMOUNT KEYBOARD



**\$650.00 USD**

### ***Vandal Resistant Panelmount Keyboard with Built-in Trackball Mouse***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
  - Rugged, Vandal Resistant Panelmount Keyboard
    - NVIS-compliant Red Backlighting
    - 10 Million Actuations Expected life
  - 71 Full Travel, Tactile Laser Etched Keys
    - Includes 5.75' USB cable
  - Desktop version also available.



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model KYBX-400 series keyboard is an industrial grade Vandal Resistant Panelmount Keyboard with built-in optical trackball that is environmentally sealed to NEMA 4, 4X, IP65 specifications when installed properly. This rugged keyboard is housed in a rugged vandal resistant enclosure and will stand up to harsh, wet and dirty environments.

This Stealth keyboard features 71 full-travel keys with silent tactile feedback for fast and accurate data input functionality. The 38mm optical trackball is sealed to NEMA 4, 4X / IP65 environmental specifications and offers a superior resolution of 800DPI.

Stealth's line of rugged kiosk/indestructible Keyboards also features NVIS-compliant red backlighting, which makes this keyboard ideal for military, aviation or vehicle applications where night vision goggles are worn. Ideal applications include in vehicle computing, plant floor, kiosks, control rooms, warehousing and outdoor environments to name a few.

## ADDITIONAL INFORMATION

### Industrial Approvals

Meets NEMA 4, 4X, IP65 when installed properly\* RoHS Compliant, CE and FCC

Material: Polymer

Style: Protuberant rectangular keys

Life: >10 million actuations

### Key Switch

Travel: 2.00mm (0.07")

Contact: Carbon-on-Gold key switch PCB

Trackball: 38mm (1.5") diameter

800 DPI IP65 Optical Trackball Mouse

### Power

Supply Voltage: +5V DC +/-5%

Current Rating: Approx. 30mA

Operating: -20C to +60C (-4F to +140F)

Storage: -40C to +70C (-40F to +158F)

### Temperature Range

Atmospheric pressure: 60-106Kpa.

Saline mist: 96 hours, IEC 60512-6

Damp heat test at + 40oC: 21 days, IEC 60512-6

Dry heat test at + 85oC: 10 days, IEC 60512-6

### Humidity

30-90%

### Housing

Rugged, Vandal Resistant Stainless Steel casing

Sealed to NEMA 4, 4X, IP65 when installed properly

### Backlighting / Illumination

NVIS-compliant red backlighting, ideal for military, aviation or vehicle applications

### Dimensions

(W-H-D) 14.96" x 4.64" x 1.43" (380.0mm x 118mm x 36.5mm)

### Cable

Length: 5.75 feet (1.75m)

Design: Single Cable USB

### Compatibility

Compatible with all Windows Operating Systems

### Warranty

1 Year limited Warranty Standard

### Model Numbers

KYBX-400-PM-BL-TB-USB (USB Interface)

### Disclaimer

Note: Specifications are subject to change without notice.