

1535-FTM-OEM - OEM/OPEN-FRAME POINTING DEVICE



\$170.00 USD

Open-Frame Pointing Device Mouse

- Meets NEMA 4, 4X / IP65 specifications when properly installed
- Three-button version of the OEM/Open-Frame FingerTipMouse (Pointing Device)
 - Sensor Moves on 10 Degree Tilt for 360 Degree Movement
 - 10 Million cycles expected life
 - Ideal for Kiosk Applications
 - Includes 6' cable PS/2 or USB interface



PRODUCT DESCRIPTION

The Stealth Computer model 1535-FTM-OEM is an OEM version of our industrial pointing device. This small unit offers the same functionality as all Stealth's industrial pointing devices. It has the same low profile design with no protruding parts.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Key Switch

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 20g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

Power

PS/2 Mouse: 10mA @ 5V (from mouse port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% Humidity Resistant when properly installed

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 1.5" x 3.5" x 0.5" (38.1mm x 88.9mm x 12.7mm)

Cable

Length: 6ft (1.83 m) - Single PS/2 or USB interface

Compatibility

Compatible with all Windows Operating Systems

Warranty

1 Year Parts & Labor

Model Numbers

1535-FTM-OEM-PS/2

1535-FTM-OEM-USB

Disclaimer

Note: Specifications are subject to change without notice.