

1535-UHP-PS/2 - OEM/OPEN-FRAME POINTING DEVICE (DISCONTINUED)



Open-Frame Pointing Device Mouse

- Meets NEMA 4, 4X / IP65 specifications when properly installed
 - ABS-Polycarbonate Sealed Plastic Case
- Three-button version of the OEM/Open-Frame FingerTipMouse (Pointing Device)
 - Sensor Moves on 10 Degree Tilt for 360 Degree Movement
 - 10 Million cycles expected life
 - Ideal for Kiosk Applications
 - Includes 10' cable PS/2 or USB interface

(Important Notice: The 1535-UHP-PS/2 model is now end of life and is replaced by the functional equivalent model 1535-FTM-OEM.)



PRODUCT DESCRIPTION

The Stealth Computer model 1535-UHP-PS/2 is the OEM version of the Hula pointing device industrial pointing device offers the same functionality as the enclosed Hula pointing device. It has the same low profile design with no protruding parts.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.060" (1.5mm)

Actuation Force: 5oz (130g)

Feedback: Tactile with mechanical snap

Power

PS/2 Mouse: 10mA @ 5V (from mouse port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% Humidity Resistant when properly installed

Shock

3×11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 1.5" x 3.5" x 0.5" (38.1mm x 88.9mm x 12.7mm)

Cable

Length: 10 feet (3.94 meters), Interface: Either PS/2 or USB single connection

Compatibility

Compatible with all Windows Operating Systems

Warranty

1 Year limited Warranty Standard

Model Numbers

1535-UHP-PS/2 (PS/2 Interface)

Disclaimer

Note: Specifications are subject to change without notice.