

## 2020-UHP-PS/2 - OEM/OPEN-FRAME POINTING DEVICE (DISCONTINUED)



### ***Open-Frame Pointing Device Mouse***

- Meets NEMA 4, 4X / IP65 specifications when properly installed
  - ABS-Polycarbonate Sealed Plastic Case
- Three-button version of the OEM/Open-Frame FingerTipMouse (Pointing Device)
  - Sensor Moves on 10 Degree Tilt for 360 Degree Movement
    - 10 Million cycles expected life
    - Ideal for Kiosk Applications
  - Includes 10' cable PS/2 or USB interface

***(Important Notice: The 2020-UHP-PS/2 model is now end of life and is replaced by the functional equivalent model 2020-FTM-OEM.)***



## PRODUCT DESCRIPTION

The Stealth Computer model 2020-UHP is the OEM version of the Hula pointing device industrial pointing device offers the same functionality as the enclosed Hula pointing device.. It has the same low profile design with no protruding parts.

**ADDITIONAL INFORMATION****Industrial Approvals**

NEMA 4, 4X, IP65\* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

**Key Switch**

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.060" (1.5mm)

Actuation Force: 5oz (130g)

Feedback: Tactile with mechanical snap

**Power**

PS/2 Mouse: 10mA @ 5V (from mouse port)

**Temperature Range**

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

**Humidity**

100% Humidity Resistant when properly installed

**Shock**

3×11 ms pulses of 50g on each of 3 axes

**Vibration**

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

**Dimensions**

(W-H-D) 2.0" x 2.0" x 0.75" (50.8mm x 50.8mm x 19.1mm)

**Cable**

Length: 10 feet (3.94 meters), Interface: Either PS/2 or USB single connection

**Compatibility**

Compatible with all Windows Operating Systems

**Warranty**

1 Year limited Warranty Standard

**Model Numbers**

2020-UHP-PS/2 (PS/2 Interface)

**Disclaimer**

Note: Specifications are subject to change without notice.