

## 5000-OEM-FSR - OEM/OPEN-FRAME KEYBOARD



# \$440.00 USD

## Open-Frame keyboard, w/ Built-in Mouse

- Meets NEMA 4, 4X / IP65\* When properly installed
- 112 Keys, 20 Function Keys, 22 Key numeric keypad
  - Built-in 3 button FingerTipMouse (Pointing Device)
    - "CLEAN KEY" disengages keys for easy cleaning
      - Greater than 10 Million cycles expected life
  - Includes 10' straight cable (PS/2 or USB interface)





#### PRODUCT DESCRIPTION

The Stealth Computer model 5000-OEM-FSR combines a 112-key keyboard and built-in FingerTipMouse (pointing device) into a single, fully integrated unit. Each kit is comprised of an industrial silicone keypad, switch matrix board, keyboard controller, and cables. This keyboard also offers users the Windows keys for easy access to system shortcuts and features a "Clean Key" that locks the keyboard down when a cleaning function is performed.

Page: 2 April 23, 2024



**Industrial Approvals** 

www.stealth.com

### **ADDITIONAL INFORMATION**

NEMA 4, 4X, IP65\* when properly installed, UL/ULc 60950, CE,

FCC Class 15, Part B

\* Proper instructions must be followed to create a water-tight

seal (NEMA 4X / IP65)

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

**Key Switch** Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 35mA @ 5V (from keyboard Port)

PS/2 Mouse: 5mA @ 5V (from mouse port)

**Power** \* PS2 Current ratings valid only when both keyboard and mouse

are connected

USB Keyboard / Mouse: 40mA @ 5V from USB port

Temperature Range

Operating: -20C to +60C (-4F to +140F)

Storage: -40C to +70C (-40F to +158F)

**Humidity** 100% (when properly installed)

**Shock** 3×11 ms pulses of 50g on each of 3 axes

Vibration Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

**Dimensions** (W-H-D) 15.0" x 6.5" x 0.42" 381.0mm x 165.1mm x 10.7mm

Cable Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2

Connectors, or Single USB Cable

PS/2: All windows operating systems most Linux/Unix Systems,

**Compatibility** USB: All windows operating systems, MAC OS and most

Linux/Unix Systems

Warranty 1 Year limited Warranty Standard

Model Numbers 5000-OEM-FSR-USB (USB Interface)

5000-OEM-FSR-PS/2 (PS/2 Interface)

**Disclaimer** Note: Specifications are subject to change without notice.