

880-OEM-FSR-BL - SMALL FOOTPRINT OEM/OPEN-FRAME KEYBOARD



\$315.00 USD

Small Open-Frame keyboard, w/ Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - Backlighting / Illumination
 - Small Foot Print Design
 - 86 Keys, 12 Function Keys, Emergency Key
- Built-in 3 button FingerTipMouse (Pointing Device)
 - Greater than 10 Million cycles expected life
 - PS/2 or USB connectors



PRODUCT DESCRIPTION

The Stealth Computer model 880-OEM-FSR-BL offers both a rugged OEM keyboard and rugged computer pointing device in one compact package. The OEM-911-Mobile's backlighting boasts five levels of illumination. Additionally, the 880-OEM-FSR-BL features a specially designed Emergency key that when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. The keyboard will meet NEMA 4 specifications when properly installed.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

* Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65)

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Key Switch

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 160mA @ 5V (from keyboard Port)

PS/2 Mouse: 55mA @ 5V (from mouse port)

Power

* PS2 Current ratings valid only when both keyboard and mouse are connected

USB Keyboard / Mouse: 215mA @ 5V from USB port

Temperature Range

Operating: -20C to +60C (-4F to +140F)

Storage: -40C to +70C (-40F to +158F)

Humidity

100% (when properly installed)

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours

Backlighting / Illumination

Red LEDs, 4 levels
(On/Off, 1, 2, 3, 4)

Dimensions

(W-H-D) 11.12" x 6.05" x 0.72" (282.4mm x 153.7mm x 18.3mm)

Cable

Design: 4 Feet (1.2 meters) Single 4' "Y-Split" Coiled Cable with PS/2 Connectors, or Single USB Cable

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,
USB: All windows operating systems, MAC OS and most Linux/Unix Systems

Additional Options

Custom cable lengths, special connectors, custom enclosures etc
Other Languages Available – Contact us for more details,
Minimum quantities may apply.

Warranty

1 Year limited Warranty Standard

Model Numbers

880-OEM-FSR-BL-USB (USB Interface)

880-OEM-FSR-BL-PS/2 (PS/2 Interface)

Disclaimer

Note: Specifications are subject to change without notice.