

FTM-OEM-FSR - OEM/OPEN-FRAME INDUSTRIAL POINTING DEVICE



\$195.00 USD

Industrial Fingertip Mouse

- Meets NEMA 4, 4X, 12 specifications when properly installed
- 3-Button Mouse design, Right Left & Center / Middle buttons
- Pressure Sensitive Sensor for positive motion control, 360 Degree Movement
 - 10 Million cycles expected life
 - Ideal for Kiosk Applications
- Includes 10' cable PS/2 or USB interface



PRODUCT DESCRIPTION

The Stealth Computer model FTM-OEM-FSR is the OEM version of the industrial Fingertip mouse. It offers the same functionality as the enclosed FTM-DT-FSR and panel mount FTM-PM-FSR. It has the same low profile design with no protruding parts.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

* Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65)

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

Key Switch

Power

PS/2: 35mA @ 5V (from mouse Port)

USB: 35mA @5V (from USB port)

Temperature Range

Operating: -20C to +60C (-4F to +140F)

Storage: -40C to +70C (-40F to +158F)

Humidity

100% Humidity Resistant when properly installed

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-D-H) 3.7" x 3.7" x 0.54" (93.98mm x 93.98mm x 13.71mm)

Cable

Length: 10 feet (3.94 meters), Design: PS2 or USB

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems, USB:

All windows operating systems, MAC OS and most Linux/Unix Systems

Warranty

1 Year limited Warranty Standard

Model Numbers

FTM-OEM-FSR (PS/2 Interface)

FTM-OEM-FSR-USB (USB Interface)

Disclaimer

Note: Specifications are subject to change without notice.