

1000-PMU - RUGGED PANELMOUNT KEYBOARD



\$370.00 USD

Sealed Panelmount keyboard

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - ABS Polycarbonate Frame with 4-40 Mounting Studs
- 104 Keys, 12 Function Keys, WIN KEY, Numeric Keypad
 - Greater than 10 Million cycles expected life
 - PS/2 or USB connectors



PRODUCT DESCRIPTION

The Stealth Computer rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. They meet NEMA 4, 4X specifications which enables them to survive in the roughest of conditions.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.060" (1.5mm)

Actuation Force: 6.35oz +/- 1.06oz (180g+/-30g)

Feedback: Tactile with mechanical snap

Power

Keyboard: 5V@50ma (from CPU Port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% (when properly installed)

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 15.39" x 7.06" x 1.25" (390.9mm x 179.3mm x 31.8mm)

CUTPIT: 13.52" x 5.18" (343.4mm x 131.6mm)

Cable

Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most Linux/Unix Systems

Additional Options

Custom cable lengths, special connectors, custom enclosures etc

Other Languages Available – Contact us for more details,

Minimum quantities may apply.

Warranty

1 Year limited Warranty Standard

Model Numbers

1000-PMU-PS/2 (PS/2 Interface)

1000-PMU-USB (USB Interface)

Disclaimer

Note: Specifications are subject to change without notice.