

## 5000-PMU-TP2 - RUGGED PANELMOUNT KEYBOARD




**\$500.00 USD**

### ***Panelmount keyboard, w/ Built-in Mouse***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
  - ABS Polycarbonate Frame with 4-40 Mounting Studs
- 116 Keys including 24 Function Keys, 26 Key numeric keypad
  - Built-in Touchpad Pointing Device Mouse
  - "CLEAN KEY" disengages keys for easy cleaning
  - Greater than 10 Million cycles expected life
    - PS/2 or USB connectors



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth Computer rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. They meet NEMA 4, 4X / IP65 specifications which enables them to survive in the roughest of conditions.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

## ADDITIONAL INFORMATION

### Industrial Approvals

NEMA 4, 4X, IP65\* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

### Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 6.35oz +/- 1.06oz (180g+/-30g)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 50mA @ 5V (from keyboard port)

### Power

PS/2 Mouse: 10mA @ 5V (from mouse port)

USB Keyboard / Mouse: 60mA @ 5V (from USB port)

### Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

### Humidity

100% (when properly installed)

### Shock

3x11 ms pulses of 50g on each of 3 axes

### Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

### Dimensions

(W-D-H) 15.39" x 7.06" x 0.50" (390.9mm x 179.32mm x 12.7mm)

### Cable

Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable

### Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most Linux/Unix Systems

### Warranty

1 Year limited Warranty Standard

### Model Numbers

5000-PMU-TP2-PS/2 (PS/2 Interface)

5000-PMU-TP2-USB (USB Interface)

### Disclaimer

Note: Specifications are subject to change without notice.