

18-PM-FTM - PANELMOUNT NUMERIC KEYPAD WITH MOUSE (DISCONTINUED)



Panelmount Numeric Keypad with built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed
- 18 key numeric layout with Enter, Escape, and Arrow (numlock) key functionality.
 - 2-Button Pointing Device Mouse
 - Ideal for Kiosk Applications
 - 10 Million cycles expected life
 - PS/2 or USB connectors

The model 18-PM-FTM is now End-of-Life, if you have a requirement please contact us or see our current lineup of rugged keyboards & pointing devices.



PRODUCT DESCRIPTION

The Stealth Computer model 18-PM-FTM provides a full numeric keypad that is easily integrated into any system. The secondary legend can be accessed by pressing the NumLock key. The 18-PM-FTM further increases its versatility with the 2-button industrial pointing device. It is also possible to cascade a secondary keyboard if needed.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals

NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC Class 15, Part B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 135g (+/- 30g), 4.76 oz. +/- 1.06 oz.

Feedback: Tactile with mechanical snap

Power

PS/2 and USB Keyboard: 40mA (from Keyboard or USB Port)

USB Mouse: 35mA @ 5V (from USB Port)

PS/2 Mouse: 35mA @ 5V (from Mouse Port)

Temperature Range

Operating: -40C to +70C (-40F to +158F)

Storage: -40C to +90C (-40F to +194F)

Humidity

100% Humidity Resistant

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 5.85" x 8.51" x 0.75" (148.6mm x 216.2mm x 19.1mm)

Cable

Individual Cables

Length: 10' (3.04 meters)

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most Linux/Unix Systems

Warranty

1 Year limited Warranty Standard

Model Numbers

18-PM-FTM-PS/2 (PS/2 Interface)

18-PM-FTM-USB (USB Interface)

Disclaimer

Note: Specifications are subject to change without notice.