

## FTM-DT-FSR - DESKTOP INDUSTRIAL POINTING DEVICE



**\$250.00 USD**

### ***Desktop Industrial Fingertip Mouse***

- Desktop or Bench Top style
- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Rugged Sealed Stainless Steel
- 3-Button Mouse design, Right Left & Center / Middle buttons
- Pressure Sensitive Sensor for positive motion control, 360 Degree Movement
  - 10 Million cycles expected life
- Includes 10' cable PS/2 or USB interface



## **PRODUCT DESCRIPTION**

The Stealth FTM-DT-FSR is an environmentally sealed, NEMA 4, 4X / IP65, desktop pointing device that is designed to operate in wet, dirty or harsh environments. Housed in water-tight durable stainless steel enclosure, this industrial grade pointing device combines the functionality of a mouse with the ease of a joystick in a small tough package.

The FTM-DT-FSR is available with USB or PS/2 cable sets. All of Stealth's industrial grade keyboards and pointing devices are plug-and-play compatible with Windows operating systems and require no special drivers.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

## ADDITIONAL INFORMATION

### Industrial Approvals

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

### Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

### Power

PS/2: 35mA @ 5V (from mouse Port)

USB: 35mA @5V (from USB port)

### Temperature Range

Operating: -20C to +70C (-4F to +158F)

Storage: -40C to +70C (-40F to +158F)

### Humidity

100% Humidity Resistant when properly installed

### Shock

3x11 ms pulses of 50g on each of 3 axes

### Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

### Dimensions

(W-D-H) 4.9" x 4.9" x 1.13" (124.5mm x 124.5mm x 28.7mm)

### Cable

Length: 10 feet (3.94 meters), Design: PS2 or USB

### Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most Linux/Unix Systems

### Warranty

1 Year limited Warranty Standard

### Model Numbers

FTM-DT-FSR-PS/2 (PS/2 Interface)

FTM-DT-FSR-USB (USB Interface)

### Disclaimer

Note: Specifications are subject to change without notice.