5000-DT-FSR - STAINLESS STEEL INDUSTRIAL DESKTOP KEYBOARD



$625.00 USD

Rugged Sealed Stainless Steel Keyboard, w/ Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
- Rugged Stainless Steel Case
- 116 Keys including 24 Function Keys, 26 Key numeric keypad
- Built-in 3 button FingerTipMouse (Pointing Device)
- "CLEAN KEY" disengages keys for easy cleaning
- Greater than 10 Million cycles expected life
- Includes 10' cable (specify PS/2 or USB)

GALLERY IMAGES





PRODUCT DESCRIPTION

The Stealth Computer stainless steel rugged industrial keyboard model 5000-DT-FSR combines a FingerTipMouse (pointing device) and a 116-key keyboard, to provide dual functionality in one compact unit. This keyboard also offers users the Windows keys for easy access to system shortcuts and features a "Clean Key" that locks the keyboard down when a cleaning function is performed.

Stealth has a wide variety of rugged industrial keyboards & pointing devices and have been designed for use in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
Key Switch	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
Power	PS/2 Keyboard: 35mA @ 5V (from keyboard Port) PS/2 Mouse: 5mA @ 5V (from mouse port) * PS2 Current ratings valid only when both keyboard and mouse are connected USB Keyboard / Mouse: 40mA @ 5V from USB port
Temperature Range	Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
Humidity	100%
Shock	3×11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Dimensions	(W-H-D) 16.25" x 7.88" x 1.8" (412.8mm x 200.2mm x 45.7mm)
Cable	Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable
Compatibility	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
Additional Options	Custom cable lengths, special connectors, custom enclosures etc Other Languages Available – Contact us for more details, Minimum quantities may apply.
Warranty	1 Year limited Warranty Standard
Model Numbers	5000-DT-FSR-PS/2 (PS/2 Interface) 5000-DT-FSR-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.