# STEALTHMOUSE - DESKTOP WATERPROOF MOUSE



## $175.00 USD

***Rugged Waterproof Mouse***

- Optical, NEMA 4X / IP65 Waterproof Mouse
- Smooth-Surface Buttons
- Optical Tracking Technology
- Comfortable, Ergonomic Design
- Features a sealed, industrial silicone overlay and robust ABS polycarbonate frame
- USB connector and adapter for PS/2

## PRODUCT DESCRIPTION

The StealthMOUSE is an optical, waterproof mouse suited for industrial, medical, marine applications or environments that contain dust, moisture or other liquids that your typical office mouse can't stand up to. Stealth's rugged pointing device is constructed from an industrial silicone overlay and durable polycarbonate frame.

Like Stealth's industrial keyboards and pointing devices this optical mouse also meets NEMA 4X/ IP65 standards. The reliable optical technology provides for pinpoint accuracy functioning on most surfaces. The StealthMOUSE has two "click" buttons and comes with a standard USB connector and a PS/2 adapter. The StealthMOUSE is plug and play, Microsoft compatible requiring no special drivers to operate.

## ADDITIONAL INFORMATION

| | |
|---|---|
| **Industrial Approvals** | NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B |
| **Key Switch** | Material: Industrial Silicone Rubber<br>Feedback: Tactile with mechanical snap |
| **Power** | 5V@50ma (from mouse conn. port) |
| **Temperature Range** | Operating: -40C to +60C (-40F to 140F)<br>Storage: -40C to +90C (-40F to +194F) |
| **Humidity** | 100% |
| **Shock** | 3×11 ms pulses of 50g on each of 3 axes |
| **Vibration** | Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,<br>Duration of Test per Axis: 3 hours |
| **Dimensions** | (W-H-D) 2.58" x 1.56" x 5.0" 65.5mm x 39.7mm x 127.0mm |
| **Cable** | Length: 6 feet, Design: PS/2 or Single Cable USB |
| **Compatibility** | Compatible with all Windows Operating Systems |
| **Warranty** | 1 Year limited Warranty Standard |
| **Model Numbers** | StealthMOUSE-PS/2 (PS/2 Interface)<br>StealthMOUSE-USB (USB Interface) |
| **Disclaimer** | Note: Specifications are subject to change without notice. |