

### **15.6" ZERO BEZEL PANEL MOUNT LCD WIDESCREEN DISPLAY (DISCONTINUED)**



#### Model: SVZ-1560-PM-PCT

- Sealed Front Panel Design to NEMA 4/IP65
  - Multi-Touch (PCT / PCAP) Touchscreen
  - Full HD 1080p, 1920 x 1080 resolution
    VGA/HDMI/DVI video connectors
  - Easy to Service & Maintain in the field
    - LED Backlight

This product has been discontinued, if you are still interested in this product and have a requirement please contact us.



### **GALLERY IMAGES**





## **PRODUCT DESCRIPTION**

Stealth's 15.6" Zero Bezel Panel Mount LCD Widescreen Display with multi-touch PCAP Touchscreen features a zero bezel, edge to edge design that eliminates dust and debris build-up at the edge and corners of the display.

Stealth's Zero Bezel Display is equipped with an environmentally sealed NEMA 4/IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. The Stealth model SVZ-1560-PM-PCT easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications.

The Zero Bezel LCD series utilizes Projected Capacitive touchscreen technology (PCAP) allowing for a modern user interface thereby making use of new and extended ways of user input and control. Gesture-based interactions by touching and pointing, with one finger or more, rotate, pinch to zoom and move objects on the display.

From the factory floor to the stock market floor, this unit provides the touchscreen capabilities necessary for multiple fast-paced environments.

Stealth offers a wide range of Rugged LCD displays offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products yet customizable in 8.4" up to 26" diagonal sizes.



# **ADDITIONAL INFORMATION**

Bezel Type	Panel Mount
Screen Size	15.6" Diagonal
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.17925 x 0.17925
Luminance (Brightness)	400 cd/m2 typical at center (400 Nits)
Contrast Ratio	500:1 (Typical)
Viewing Angle	70 (up), 70 (down), 60 (left), 60 (right)
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI
Touchscreen Interface	1x USB 2.0
Unit Weight	10.9 lbs.
Dimensions	Panel Mount: 15.61" x 9.90" x 2.79"
Panel Finish	Zero Bezel Design
Housing	Aluminum
Mounting	Panel mount / VESA 100 x100
Power Input	Input is 12VDC +/-5%
Power Supply	110-240AC to 12V DC out 50W
Environmental Rating	Front: IP65 Rear: IP20 / Fanless
Environmental	Non-Operating Temperature: -20~60° Operating Temperature: 0~50° Shock: 30g, 11ms, 1/2 sine Vibration: 1g RMS 20-500 Hz Relative Humidity: 10% ~ 90% non-condensing (Operating & Non-Operating)
Approvals	RoHS



Available Models	SVZ-1560-PM-PCT - Multi-Touch (PCT / PCAP) Touchscreen
Warranty	1 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.