

## 15" OPEN-FRAME LCD MONITOR - SV-1505-OEM



**\$1,025.00 USD**

***Model: SV-1505-OEM***

- 15" OEM/Open-Frame LCD Monitor
  - Easily installs in kiosks, cabinets, walls, panels & consoles
- Optional Resistive Touch Screen c/w USB and Serial Connections
  - Wide Viewing Angles
- DVI-I, HDMI, DisplayPort video connectors
- UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 Listed
  - FCC, CE, RoHS Compliant
  - 3 Year Warranty



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's 15" Open-Frame LCD Monitor is designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive or capacitive touchscreens, or without a front overlay.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 listed.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our industrial LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Open-Frame
<b>Screen Size</b>	15.0" (Diagonal)
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1024 x 768 (Auto sync from 800 x 600 to 1024 x 768)
<b>Horizontal Frequency</b>	42.9 ~ 58.8KHz (48.363 KHz typical)
<b>Vertical Frequency</b>	55 - 70Hz (60Hz typical)
<b>Pixel Pitch</b>	0.297mm x 0.297mm
<b>Response Time</b>	16ms Rise (Typical) 7ms Fall (Typical)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Video Input Connectors</b>	DVI-I VGA via DVI-VGA Adapter (Included) HDMI Displayport
<b>Viewing Angle</b>	88°/88°/88°/88° (Typical)
<b>Contrast Ratio</b>	2000:1 (typical)
<b>Luminance (Brightness)</b>	300 cd/m2 typical at center (300 Nits)
<b>Viewable Image Size</b>	Horizontal: 11.97" / 304.1 mm, Vertical: 8.98" / 228.1 mm
<b>Input</b>	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) DC Input: 9V - 36V DC DC Input: 43V - 160V DC DC Input: 180V - 300V DC AC Adapter is Removable
<b>Control Buttons (Rear mounted)</b>	Power, Left, Right, Menu

<b>Controls On-Screen Display</b>	Brightness
	Color
	Image Adjust
	Input Source
	OSD Lockout
	Sound (not applicable)
<b>Environmental Rating</b>	Tools
	N/A – not rated
<b>Environmental</b>	Operating Temperature: -10C – +60C (14F – 140F)
	Storage Temperature: -30C – +85C (-22F – +185F)
	Operating: Relative Humidity 20% ~ 80%
	Storage Relative Humidity: 20% ~ 80%
<b>Panel Finish</b>	N/A – Open-Frame
<b>Unit Weight</b>	Unit Weight: 9.15 Lbs (4.14 Kg)*
	Shipping Weight: 14.85 Lbs (6.72 Kg)*
	* Weight may vary depending on configuration
<b>Dimensions</b>	Add 1.33" (33.78mm) to depth with rear mounted AC Adapter
	With Touch: 15.01" x 11.23" x 2.3" (381.20mm x 285.24mm x 58.38mm) [W x H x D]
	Without Touch: 15.01" x 11.23" x 1.94" (381.20mm x 285.24mm x 49.38mm) [W x H x D]
	CSA C22.2#62368-1:2019 Ed.3
<b>Approvals</b>	UL 62368-1:2019 Ed.3
	RoHS
	CE
<b>Cooling</b>	FCC
	Natural Convection (no fan)
	SV-1505-OEM – No Touch Included, 9~36V DC Input, AC Adapter Included
	SV-1505-OEM-160V – No Touch Included, 43~160V DC Input
	SV-1505-OEM-300V – No Touch Included, 180~300V DC Input
<b>Available Models</b>	SV-1505-OEM-RT – Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Included
	SV-1505-OEM-RT-160V – Resistive Touch (Serial/DB9 and USB), 43~160V DC Input
	SV-1505-OEM-RT-300V – Resistive Touch (Serial/DB9 and USB), 180~300V DC Input
<b>Warranty</b>	3 Year Parts and Labor

## Disclaimer

Note: Specifications are subject to change without notice.