

15" OPEN-FRAME LCD MONITOR - SV-1510-OEM (DISCONTINUED)




Model: SV-1510-OEM

- 15" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
- Resistive Touch Screen Standard c/w USB and Serial Connections
 - Optional Capacitive Touchscreen
 - Wide Viewing Angles
 - VGA & DVI-D video connectors
 - cULus Listed
 - 1 Year Warranty

(Important Notice: The SV-1510-OEM model is now end of life and is replaced by the functional equivalent model SV-1505-OEM.)



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 15" Open-Frame LCD Monitor is designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive/capacitive touchscreens or without a front overlay.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
Horizontal Frequency	37.9 kHz ~ 62.4 kHz
Vertical Frequency	48.8 kHz ~ 75.1 Hz
Pixel Pitch	0.297mm x 0.297mm
Response Time	35 ms
Type	LCD c/w LED Backlighting Backlight Life: 50,000 Hrs Typical
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	65 (up), 85 (down), 85 (left), 85 (right)
Contrast Ratio	1500:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 11.97" / 304.1 mm, Vertical: 8.98" / 228.1 mm
Input	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) 12V DC Power Jack at LCD
Control Buttons (Rear mounted)	Power Switch, Menu/Select, Exit/Back, Select (+,-), Auto, Hot Brightness (+,-)
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	OEM/Open-Frame chassis - not rated

Environmental

Operating Temperature: 0 - 40C (32 to 104 F)
Storage Temperature: 0~60C (32~140F)
Relative Humidity: 10% ~ 90% non-condensing (Operating & Non-Operating)
Operating Altitude: 0 to 10,000 ft.
Storage Altitude: 0 to 40,000 ft.

Shock

30g's, 11ms, ½ Sine

Vibration

1g RMS, 20-500Hz

Approvals

cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07

Cooling

Natural Convection (no fan)

Panel Finish

Black Baked Enamel (Standard)
Stainless Steel - Brushed #304 (Optional)

Unit Weight

Unit Weight: 7 Lbs (3.2kg) without touchscreen
Unit Weight: 8 Lbs (3.6kg) with touchscreen

Dimensions

For Dimensions please refer to the OEM Dimensional Drawing

Available Models

SV-1510-OEM: Open Frame unit with AC power input

Warranty

1 Year Parts & Labor
1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.