


15" PANEL MOUNT LCD MONITOR - SV-1505-PM



\$1,585.00 USD

Model: SV-1505-PM

- Panel Mount LCD, 15" Industrial Grade
- NEMA 4/4X / IP66 Environmentally Sealed
- Resistive Touch Screen Standard c/w USB and Serial Connections
 - Optional Capacitive Touch with USB interface
 - Wide Viewing Angles
- Stainless Steel (NEMA 4X / IP66) & Custom painted bezel options
 - DVI-I, HDMI, DisplayPort video connectors
- UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 Listed
 - FCC, CE, RoHS Compliant
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth builds high quality LCD monitors suited for industrial and commercial applications. Our 15" Panel Mount LCD Monitor comes equipped with an environmentally sealed NEMA 4/4X / IP66 front panel that is resistant to splashes or hose downs. All Stealth Panel Mount LCD products are easily installed by securing the rear studs into your console, panel or wall.

The SV-1505-PM panel mount lcd comes equipped with a Resistive Touch Screen standard.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 listed.

We offer Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Stealth's LCD products are environmentally sealed to NEMA 4 (4X with Stainless Steel bezel) / IP66 and are ideal for applications where dirt, dust, moisture and water are present. Stealth's rugged LCD products are constructed from solid steel and stainless steel for corrosion resistance applications.

ADDITIONAL INFORMATION

Bezel Type	Panel Mount
Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768 (Auto sync from 800 x 600 to 1024 x 768)
Horizontal Frequency	42.9 ~ 58.8KHz (48.363 KHz typical)
Vertical Frequency	55 - 70Hz (60Hz typical)
Pixel Pitch	0.297mm x 0.297mm
Response Time	16ms Rise (Typical) 7ms Fall (Typical)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	DVI-I VGA via DVI-VGA Adapter (Included) HDMI Displayport
Viewing Angle	88°/88°/88°/88° (Typical)
Contrast Ratio	2000:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Viewable Image Size	Horizontal: 11.97" / 304.1 mm, Vertical: 8.98" / 228.1 mm
Input	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) DC Input: 9V - 36V DC DC Input: 43V - 160V DC DC Input: 180V - 300V DC AC Adapter is Removable
Control Buttons (Rear mounted)	Power, Left, Right, Menu

	Brightness
	Color
	Image Adjust
Controls On-Screen Display	Input Source
	OSD Lockout
	Sound (not applicable)
	Tools
	Standard Bezel: NEMA 4/4X / IP66 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water
Environmental Rating	Optional Stainless Steel Bezel: NEMA 4X / IP66 Front Panel (when properly installed) corrosion protection, protection against windblown dust and rain, splashing water, and hose-directed water
	Operating Temperature: -10C - +60C (14F - 140F)
Environmental	Storage Temperature: -30C - +85C (-22F - +185F)
	Operating: Relative Humidity 20% ~ 80%
	Storage Relative Humidity: 20% ~ 80%
Panel Finish	Black Baked Enamel (Standard)
	Stainless Steel - Brushed #304 (Optional)
Unit Weight	Unit Weight: 12 Lbs (5.4kg)
Dimensions	Add 1.33" (33.78mm) to depth with rear mounted AC Adapter
	Panel Mount: 16.38" x 14.00" x 2.31" (415.93mm x 355.60mm x 58.68mm) [W x H x D]
	CSA C22.2#62368-1:2019 Ed.3
Approvals	UL 62368-1:2019 Ed.3
	RoHS
	CE
	FCC
Cooling	Natural Convection (no fan)

Available Models

SV-1505-PM-RT – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Included

SV-1505-PM-RT-160V – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 43~160V DC Input

SV-1505-PM-RT-300V – Painted Bezel, Resistive Touch (Serial/DB9 and USB), 180~300V DC Input

SV-1505-PM-RT-SS – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 9~36V DC Input, AC Adapter Included

SV-1505-PM-RT-SS-160V – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 43~160V DC Input

SV-1505-PM-RT-SS-300V – Stainless Steel Bezel, Resistive Touch (Serial/DB9 and USB), 180~300V DC Input

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.