

17.3" MULTI-TOUCH PANEL MOUNT LCD MONITOR (DISCONTINUED)



Model: SV-1730AW-PM-PT-USB

- Panel Mount 17.3" Widescreen LCD Monitor
 - NEMA 4 Environmentally Sealed
 - Multi-Touch (PCT / PCAP) Touchscreen,

USB Interface, 2 Point Touch

- PIP (Picture-In-Picture)
 - 16:9 Aspect Ratio
- 1920 x 1080 Maximum Resolution
 - 300 Nits of Brightness
 - Wide Viewing Angles
- DisplayPort, DVI-D, Composite & S-Video connectors
 - 2 Year Warranty

The SV-1730AW-PM-PT-USB is now End of Life, please contact us if you have a requirement.





GALLERY IMAGES







PRODUCT DESCRIPTION

Stealth's 17.3" Multi-Touch Panel Mount LCD Monitor features Projected Capacitive (PCAP) Touchscreen, the same technology found in smart phones and tablets but equipped for your industrial application. The Stealth model SV-1730AW-PM-PT-USB easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications.

Using Projected Capacitive touchscreen technology (PCAP) allows for a modern user interface thereby making use of new and extended ways of user input and control. Gesture-based interactions by touching and pointing, with one finger or more, rotate, pinch to zoom and move objects on the display.

All Stealth Panel Mount LCD products come standard with an environmentally sealed NEMA 4 front panel that is resistant to dust/dirt penetration or even liquid splashes. The SV-1730AW-PM-PT-USB also features a 1920 x 1080 Maximum Resolution (Full HD 1080p), PIP (Picture-In-Picture) capability and DisplayPort, DVI-D, Composite & S-Video connectors.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.



ADDITIONAL INFORMATION

Bezel Type Panel Mount

Screen Size 17.3" (Diagonal)

Aspect Ratio 16:9

Native Resolution 1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)

Pixel Pitch 0.1989mm x 0.1989mm

Response Time 40ms Typical

Type LCD c/w LED Backlighting

DVI Compliant Digital HDCP (DVI-D)

Video Input Connectors

Displayport
Composite

S-video

Viewing Angle 60 (up), 80 (down), 80 (left), 80 (right)

Contrast Ratio 600:1 (typical)

Luminance (Brightness) 400 cd/m2 typical at center (400 Nits)

Viewable Image Size Horizontal: 15.04" / 381.89mm, Vertical: 8.46" / 214.812mm

Video Signal ANALOG: 0.7 Vp-p/75 Ohms

Horizontal Sync: Positive/Negative

Sync Signal Vertical Sync: Positive/Negative

Composite Sync: Positive/Negative

Standard Bezel: NEMA 4 Front Panel (when properly installed)

Environmental Rating protection against windblown dust and rain, splashing water, and

hose-directed water

Operating Temperature: 0~50C (32~122F)

Operating Humidity: 10 to 90% (non-condensing) Storage Humidity: 10 to 90% (non-condensing)

Environmental Storage Humidity: 10 to 90% (non-co Operating Altitude: 0 to 10,000 ft.

Storage Altitude: 0 to 40,000 ft.

Shock 30g's, 11ms, ½ Sine

Vibration 1g RMS, 20-500Hz



90-264VAC, 47-63Hz internal Power Supply, Auto-switching

Input Main Power switch

2A field replaceable fuse

Cooling Fans Single rear mounted intake cooling fan with dust filter

Control Buttons (Rear

mounted)

Power, Menu/OK, Check(Exit), Up and Down

Controls On-Screen Display

Image Select, Image Adjustment, Color Adjustments, Video

Settings, Scaling Adjustment, System Settings

Picture In Picture Options

(PiP)

Small, Medium, Large, Side by Side

Panel Finish Black Front Panel Finish

Unit Weight Unit Weight: 17.55lbs (7.96Kg)

Unit: 18.31" (W) x 11.75" (H) x 2.50" (D) (465.12mm x

Dimensions 298.45mm x 63.50mm)

Cutout: 17.44" (W) x 10.87" / (443mm x 276mm)

Available Models

SV-1730AW-PM-PT-USB – Multi-Touch (PCT / PCAP) Touchscreen

with USB Interface

Warranty 2 Year Parts & Labor

Disclaimer Note: Specifications are subject to change without notice.

Page: 4 April 16, 2024