

17" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1705)




\$1,890.00 USD

Model: TT-1705

- 17" Rugged Metal Enclosed Industrial LCD Monitor
 - NEMA 4, IP65 - Sealed front panel
- Resistive or Capacitive Touch Screen Options
 - Supports VESA 100mm Mounting
 - 17.0" Active Display Area
 - Wide range DC input (9 - 36V DC)
 - Wide Operating Temp (-10C - +60C)
- Ideal for use in industrial and commercial environments
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's TT-1705 is a 17" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display is available with resistive or capacitive touch screen options and includes support for wide range DC input (9 - 36V DC) and extended operating temperature of -10C - +60C (14F - 140F).

The TT-1705 comes standard with a 3 Years Warranty and also features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

In addition to our Rugged Desktop Displays, Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.5" up to 24" diagonal sizes.

ADDITIONAL INFORMATION

Screen Size	17.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.264mm x 0.264mm
Response Time	30ms (Typical)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 13.3" / 337.92 mm, Vertical: 10.6" / 270.34 mm
Input	AC Adapter is Removable DC Input: 9V - 36V DC AC Input: 100-240V, 50-60Hz, 1.5A
Control Buttons (Rear mounted)	Power, Left, Right, Menu
Controls On-Screen Display	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
LCD Mounting Options	Rear VESA 100mm Mounting Front bezel only
Environmental Rating	Meets NEMA 4 / IP65 Protection against windblown dust, rain, splashing water, and hose-directed water
Environmental	Operating Temperature: -10C - +60C (14F - 140F) Storage Temperature: -30C - +85C (-22F - +185F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%

Panel Finish	Black Powder Coated
Unit Weight	Shipping Weight: 18.0 Lbs (8.17Kg) Unit Weight: 12.5 Lbs (5.7Kg)
Dimensions	16.52" x 13.48" x 4.45" (419.73mm x 342.51mm x 112.95mm) Without Mounted AC Adapter: 16.52" x 13.48" x 3.04" (419.73mm x 342.51mm x 77.22mm)
Available Models	TT-1705-CT-DB9 - Capacitive (Serial/DB9) TT-1705-CT-USB - Capacitive (USB) TT-1705-RT - Resistive (USB and Serial/DB9)
Warranty	3 Year Parts and Labor
Disclaimer	Note: Specifications are subject to change without notice.