

17" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1706)



\$2,355.00 USD

Model: TT-1706

- 17" Rugged Metal Enclosed Industrial LCD Monitor
 - Resistive Touch Screen Standard
 - Supports VESA 100mm Mounting
 - 17.0" Active Display Area
 - Wide range DC input (9 - 36V DC)
 - Wide Operating Temp (-10C - +50C)
- Ideal for use in industrial and commercial environments
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's TT-1706 is a 17" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display can be configured with a resistive touch screen (standard) or a Capacitive Touchscreen (optional). Additional features include a wide ranging DC input (9 - 36V DC) with an external AC Power Adapter. An optional 43~160V DC power input is also available. An extended operating temperature of -10C - +50C (14F - 122F) and a 3-Year Warranty are also included.

The TT-1706 features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

In addition to our Rugged Desktop Displays, Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs available in up to 24" diagonal sizes.

ADDITIONAL INFORMATION

Screen Size	17.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.264mm x 0.264mm
Response Time	30ms (Typical)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	DVI-I c/w DVI to VGA Adapter HDMI Displayport
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 13.3" / 337.92 mm, Vertical: 10.6" / 270.34 mm
Input	DC Input: 9V - 36V DC AC Adapter is Removable AC Input: 100-240V, 50-60Hz, 1.5A
Control Buttons (Rear mounted)	Power, Left, Right, Menu
Controls On-Screen Display	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
LCD Mounting Options	Rear VESA 100mm Mounting
Environmental	Storage Temperature: -30C - +85C (-22F - +185F) Operating Temperature: -10 to 50C (14 to 122 F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
Panel Finish	Black Powder Coated
Unit Weight	Shipping Weight: 18.0 Lbs (8.17Kg) Unit Weight: 12.5 Lbs (5.7Kg)

Dimensions

16.52" x 13.48" x 4.45" (419.73mm x 342.51mm x 112.95mm)
Without Mounted AC Adapter: 16.52" x 13.48" x 3.04"
(419.73mm x 342.51mm x 77.22mm)

Available Models

TT-1706-RT – Resistive (USB and Serial/DB9)
TT-1706-RT-160V – Resistive Touch & 43V – 160V DC

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.