

## 19" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1906)



**\$2,205.00 USD**

***Model: TT-1906***

- 19" Rugged Metal Enclosed Industrial LCD Monitor
  - Resistive Touch Screen Standard
  - Supports 100mm VESA Mounting
  - Wide range DC input (9 - 36V DC)
  - Wide Operating Temp (-10C - +60C)
- Ideal for use in industrial and commercial environments
  - 3 Year Warranty



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's TT-1906 is a 19" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display includes a resistive touch screen interface and supports a wide range DC input (9 - 36V DC) with an external AC Power Adapter. Options are available for 43~160V DC or 180~300V DC power inputs. The product is designed to operate within an extended temperature range of -10C - +60C (14F - 140F).

The TT-1906 comes standard with a 3 Year Warranty and also features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

In addition to our Rugged Desktop Displays, Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs available in up to 24" diagonal sizes.

**ADDITIONAL INFORMATION**

<b>Screen Size</b>	19.0" (Diagonal)
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Pixel Pitch</b>	0.294mm x 0.294mm
<b>Response Time</b>	10ms (Typical, On/Off)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Video Input Connectors</b>	DVI-I c/w DVI to VGA Adapter HDMI Displayport
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	1000:1 (typical)
<b>Luminance (Brightness)</b>	350 cd/m2 typical at center (350 Nits)
<b>Viewable Image Size</b>	Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm
<b>Input</b>	90 ~ 264V AC, 47~63Hz rear-mounted (removable) Power Supply DC Input (std.): 9V - 36V DC DC Input (opt.): 43V - 160V DC DC Input (opt.): 180V - 300V DC
<b>Control Buttons (Rear mounted)</b>	Power, Left, Right, Menu
<b>Controls On-Screen Display</b>	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
<b>LCD Mounting Options</b>	Rear VESA 100mm Mounting
<b>Environmental</b>	Operating Temperature: -10C - +60C (14F - 140F) Storage Temperature: -30C - +85C (-22F - +185F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
<b>Panel Finish</b>	Black Powder Coated

**Unit Weight**

Shipping Weight: 19 Lbs (8.62 Kg)

Unit Weight: 17.55lbs (7.96Kg)

\* Weight may vary depending on configuration

**Dimensions**

18.45" x 14.56" x 2.68" (468.63mm x 369.83mm x 68.07mm)

Without Mounted Power Supply: 18.45" x 14.56" x 4.09"

(468.63mm x 369.83mm x 103.89mm)

**Available Models**

TT-1906-RT – Resistive (USB and Serial/DB9)

TT-1906-RT-160V – Resistive Touch & 43V – 160V DC

TT-1906-RT-300V – Resistive Touch & 180V – 300V DC

**Warranty**

3 Year Parts and Labor

**Disclaimer**

Note: Specifications are subject to change without notice.