

## 21.5" OPEN-FRAME LCD MONITOR (SV-2150WS-OEM)




**\$1,135.00 USD**

***Model: SV-2150WS-OEM***

- 21.5" OEM/Open-Frame Widescreen LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
  - Optional Touch Screen (Resistive)
    - 16:9 Aspect Ratio
  - 1920 x 1080 Maximum Resolution
- 250 Nits of Brightness, Adjustable Controls
- VGA, DVI-D, Displayport & HDMI connectors
  - Wide Viewing Angles, 178°
    - cULus Listed
  - 3 Year Warranty



## GALLERY IMAGES



Controls (Rear Mounted)



Connectors (Rear Mounted)

## PRODUCT DESCRIPTION

Stealth's 21.5" Open-Frame LCD is an OEM widescreen monitor that easily integrates into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting the display is accomplished by simply securing the screw holes located in the side flanges of the LCD.

The SV-2150WS-OEM LCD is available with optional resistive touchscreen, or without a front overlay whatsoever.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our Rugged LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

## ADDITIONAL INFORMATION

|                               |   |
|-------------------------------|---|
| <b>Bezel Type</b>             | Open-Frame  |
| <b>Screen Size</b>            | 21.5" (Diagonal)  |
| <b>Aspect Ratio</b>           | 16:9  |
| <b>Native Resolution</b>      | 1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)   |
| <b>Horizontal Frequency</b>   | 31.5 kHz ~ 83 kHz   |
| <b>Vertical Frequency</b>     | 56 Hz ~ 75 Hz   |
| <b>Pixel Pitch</b>            | 0.25mm x 0.25mm   |
| <b>Response Time</b>          | 6ms Typical   |
| <b>Type</b>                   | IPS LCD Panel c/w LED Backlighting  |
| <b>Video Input Connectors</b> | VGA / HD-15<br>DVI Compliant Digital HDCP (DVI-D)<br>HDMI<br>Displayport  |
| <b>Viewing Angle</b>          | 178° / 178° (H / V) - (Viewing angle of LCD panel sans touch)   |
| <b>Contrast Ratio</b>         | 1000:1 (typical)<br>25000:1 (dynamic)   |
| <b>Luminance (Brightness)</b> | 250 cd/m2 typical at center (250 Nits)  |
| <b>Viewable Image Size</b>    | Horizontal: 18.85" / 478.79 mm, Vertical: 10.68" / 271.27 mm  |
| <b>Video Signal</b>           | ANALOG: 0.7 Vp-p/75 Ohms  |
| <b>Sync Signal</b>            | Separate Sync: TTL Level (Positive/Negative)<br>Composite Sync on Green: (0.3Vp-p negative 0.7Vp-p positive)<br>Composite Sync: TTL Level (Positive/Negative)                                 |
| <b>Environmental Rating</b>   | OEM/Open-Frame chassis - not rated  |
| <b>Environmental</b>          | Operating Temperature: 0 - 40C (32 to 104 F)<br>Storage Temperature: -10 - 60C (14 to 140 F)<br>Operating: Humidity 20% ~ 80%, non-condensing<br>Storage Humidity: 10% to 85%, non-condensing |
| <b>Approvals</b>              | cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07   |

|                                       |   |
|---------------------------------------|---|
| <b>Input</b>                          | AC Input: 100 – 240VAC ~ 50-60Hz, 1.3A  |
| <b>Control Buttons (Rear mounted)</b> | Left (-), Right (+), Up, Down, Menu/Exit Reset/Eco, Input/Select, Power ON/OFF  |
| <b>Controls On-Screen Display</b>     | Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out |
| <b>Panel Finish</b>                   | N/A – Open-Frame  |
| <b>Unit Weight</b>                    | 10.25 lbs / 4.66 kg   |
| <b>Dimensions</b>                     | 20.92"(W) x 12.614"(D) x 2.21"(H) (531.36mm x 320.39mm x 56.13mm)   |
| <b>Available Models</b>               | SV-2150WS-OEM – Open Frame Only (no touch)<br>SV-2150WS-OEM-RT – Resistive (USB and Serial / DB9)                                       |
| <b>Warranty</b>                       | 3 Year Parts and Labor  |
| <b>Disclaimer</b>                     | Note: Specifications are subject to change without notice.  |